

Sandblast

**EHC500**

Sandblast – 60mm<sup>3</sup>



**Application**

- Conveys sand or shot for cleaning purposes
- Conveys sand from sandblast equipment to clean steel or concrete before painting or sealing
- For blasting metal, stone and concrete

**Markets**

- Construction
- Metal working
- Ship building

**Construction**

**Tube** Static dissipating SBR rubber blend

**Reinforcement**

High-tensile synthetic textile with anti-static copper wire

**Cover**

Abrasion, ozone and weather resistant pin-pricked SBR rubber blend

**Color** Black

**Certification**

TS 5928 - EN ISO 3861

**Operating temperature**

-40°C to +70°C  
(-40°F to +158°F)

Abrasion loss value acc. DIN53516 ≤60mm<sup>3</sup>

Number	Hose I.D.		Hose O.D.		Operating Pressure		Min. Burst Pressure		Minimum Bend Radius		Weight		Length	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft	mtr	ft
EHC500-08BK	12.7	0.50	25	0.98	12.1	175	36.0	522	65	2.55	0.41	0.28	61	200
EHC500-08ABK	12.7	0.50	27	1.06	12.1	175	36.0	522	60	2.36	0.50	0.33	61	200
EHC500-10BK	16.0	0.62	28	1.10	12.1	175	36.0	522	85	3.35	0.48	0.32	61	200
EHC500-10ABK	16.0	0.62	30	1.18	12.1	175	36.0	522	80	3.15	0.58	0.39	61	200
EHC500-12BK	19.0	0.75	30	1.18	12.1	175	36.0	522	100	3.94	0.49	0.33	61	200
EHC500-12ABK	19.0	0.75	31	1.22	12.1	175	36.0	522	95	3.74	0.53	0.36	61	200
EHC500-12BBK	19.0	0.75	33	1.30	12.1	175	36.0	522	90	3.54	0.65	0.44	61	200
EHC500-16BK	25.4	1.00	39	1.54	12.1	175	36.0	522	125	4.92	0.81	0.55	61	200
EHC500-20BK	32.0	1.25	48	1.89	12.1	175	36.0	522	160	6.30	1.16	0.78	61	200
EHC500-24BK	38.0	1.50	54	2.13	12.1	175	36.0	522	200	7.87	1.34	0.90	61	200
EHC500-24ABK	38.0	1.50	56	2.20	12.1	175	36.0	522	190	7.48	1.53	1.03	61	200
EHC500-28BK	44.5	1.75	60	2.36	12.1	175	36.0	522	280	11.02	1.47	0.99	61	200
EHC500-28ABK	44.5	1.75	63	2.48	12.1	175	36.0	522	270	10.60	1.82	1.22	61	200
EHC500-32BK	50.8	2.00	69	2.72	12.1	175	36.0	522	325	12.79	2.03	1.36	61	200
EHC500-32ABK	50.8	2.00	73	2.87	12.1	175	36.0	522	315	12.40	2.48	1.67	61	200
EHC500-40BK	63.5	2.50	82	3.23	12.1	175	36.0	522	400	15.70	2.63	1.77	61	200
EHC500-48BK	76.2	3.00	96	3.78	12.1	175	36.0	522	450	17.70	3.09	2.08	61	200
EHC500-64BK	101.6	4.00	122	4.80	12.1	175	36.0	522	600	23.60	4.22	2.84	61	200