

# Fittings and Ball Valve Taps

## made of Brass

- Distributors, T-Connectors, elbow-connectors and ball valve taps
- Different sizes for all kinds of application
- Robust, solid and reliable
- Maximum passage
- For water supply in industry, trades, agriculture and private households

### Materials:

- Y-Distributor, T-Connector, Elbow-Connector: Brass MS 58 plain
- Tap-housing: Brass MS 58 nickel-plated
- Handle: Aluminium red
- Balls: hard chromium plated

Max. Working Pressure	Thread	Media	Box
PN 10 bar	ISO 228	Water	5



### 2-way Distributor

Inlet	Outlet	Passage	Weight	Type No.
G 3/4 f	2 x G 3/4 m	15	85	DWS 34 Y




### T-Connector with female thread

Thread connection	L	B	Weight	Type No.
3 x G 1/2 f	51	39,5	86	TSM 12
3 x G 3/4 f	59	45,5	160	TSM 34
3 x G 1 f	75	54	250	TSM 10



### Elbow-Connector with female thread

Thread connection	L	Weight	Type No.
2 x G 1/2 f	39	83	WSM 12
2 x G 3/4 f	47	115	WSM 34
2 x G 1 f	54,5	204	WSM 10



### Ball Valve Taps, brass nickel-plated with assembled hose screwing, handle aluminium red, ball hard chromium plated

Inlet	Outlet	Hose connect.	L	L1	Weight	Type No.
G 1/2 m	G 3/4 m	Hose i.D. 13	105	55	210	WKH 12
G 3/4 m	G 1 m	Hose i.D. 19	120	55	285	WKH 34