

For the SWIVELLING version add the suffix "/SO" at the P/N, except for the 560 series.
For example:
300/20/SO

FIXED PAINTED STEEL



P/N

FIXED S. STEEL AISI 304



P/N

Supplied with:

- hose in black synthetic rubber with galvanized steel coupling
- AISI 304 stainless steel swivel joint
- Viton® seals
- central shaft in galvanized steel or stainless steel AISI 304
- inlet hose 0,6 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	P/N	Hose supplied	Connection	
				Inlet	Outlet
S. 300	300/20	302/40	without hose*	F 1/2"G	F 3/8"- 1/2"G
	300/21	302/21	12m 3/8" (953/13)	F 1/2"G	M 3/8"G
	300/22	302/22	8m 1/2" (963/8)	F 1/2"G	M 1/2"G
S. 350	350/20	352/40	without hose*	F 1/2"G	F 3/8"- 1/2"G
	350/21	352/21	17m 3/8" (953/18)	F 1/2"G	M 3/8"G
	350/22	352/22	12m 3/8" (953/13)	F 1/2"G	M 3/8"G
	350/23	352/23	10m 1/2" (963/9)	F 1/2"G	M 1/2"G
S. 430	430/20	434/20	without hose*	F 1/2"G	F 1/2"G
	430/21	432/21	10m 1/2" (963/12)	F 1/2"G	M 1/2"G
	430/22	432/22	15m 1/2" (963/14)	F 1/2"G	M 1/2"G
S. 4430 ABS	4430/20	4434/20	without hose*	F 1/2"G	F 1/2"G
	4430/21	4432/21	10m 1/2" (963/12)	F 1/2"G	M 1/2"G
	4430/22	4432/22	15m 1/2" (963/14)	F 1/2"G	M 1/2"G
S. 530	530/20	534/20	without hose*	F 1/2"G	F 1/2"G
	530/21	532/21	20m 1/2" (963/19)	F 1/2"G	M 1/2"G
	530/22	532/22	25m 1/2" (963/24)	F 1/2"G	M 1/2"G
S. 540	540/20	544/20	without hose*	F 1"G	F 1"G
	540/21**	542/21**	15m 1" (983/15)	F 1"G	M 1"G
	540/22	542/22	15m 3/4" (973/14)	F 1"G	M 3/4"G
	540/23	542/23	20m 3/4" (973/19)	F 1"G	M 3/4"G
	540/25	544/25	without hose*	F 1/2"G	F 1/2"G
	540/26	542/26	30m 1/2" (963/29)	F 1/2"G	M 1/2"G
S. 560	560/20	564/20	without hose*	F 1"G	F 1"G
	560/21	562/21	30m 3/4" (973/29)	F 1"G	M 3/4"G
	560/22	562/22	35m 3/4" (973/34)	F 1"G	M 3/4"G
	560/23	562/23	40m 3/4" (973/39)	F 1"G	M 3/4"G
	560/24**	562/24**	20m 1" (983/19)	F 1"G	M 1"G
	560/25**	562/25**	30m 1" (983/29)	F 1"G	M 1"G
	560/26	564/26	without hose*	F 1/2"G	F 1/2"G
	560/27	562/27	40m 1/2" (963/39)	F 1/2"G	M 1/2"G
	560/28	562/28	50m 1/2" (963/49)	F 1/2"G	M 1/2"G
	560/29	562/29	60m 1/2" (963/59)	F 1/2"G	M 1/2"G

Rubber handles, mounted on hose terminal part, are available for all the above series. For more information look at page 50.

** Work max pressure 50 bar, hose max working pressure 88 bar

* For the version without hose the maximum working pressure is 150 bar



Atex 94/9

II 3GD c X (only for series 300-350-4430 ABS)
IIB 2GD c T4 T135°C X