

Water max 130°C 200 bar Hygienic hose

For the SWIVELLING version add the suffix "/SO" at the P/N, except for the 560 series.
For example:
302/30/SO

FIXED S. STEEL AISI 304



Supplied with:

- hose in synthetic rubber with blue hygienic covering with galvanized steel coupling
- AISI 304 stainless steel swivel joint
- Viton® seals
- central shaft in stainless steel AISI 304
- inlet hose 0,6 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	Hygienic hose supplied	Connection	
			Inlet	Outlet
S. 300	302/30	without hose	F 3/8"G	F 3/8"G
	303/31	12m 5/16" (944/12)	F 3/8"G	F 3/8"G
S. 350	352/30	without hose	F 3/8"G	F 3/8"G
	353/31	12m 5/16" (944/12)	F 3/8"G	F 3/8"G
S. 430	434/30	without hose	F 3/8"G	F 1/2"G
	433/31	12m 3/8" (956/12)	F 3/8"G	F 3/8"G
	433/32	18m 3/8" (956/18)	F 3/8"G	F 3/8"G
S. 4430 ABS	4434/30	without hose	F 3/8"G	F 1/2"G
	4433/31	12m 3/8" (956/12)	F 3/8"G	F 3/8"G
	4433/32	18m 3/8" (956/18)	F 3/8"G	F 3/8"G
S. 530	534/30	without hose	F 3/8"G	F 1/2"G
	533/32	25m 3/8" (956/25)	F 3/8"G	F 3/8"G
S. 540	544/30	without hose	F 3/8"G	F 1/2"G
	543/31	30m 3/8" (956/30)	F 3/8"G	F 3/8"G
S. 560	564/30	without hose	F 3/8"G	F 1/2"G
	563/31	40m 3/8" (956/40)	F 3/8"G	F 3/8"G

Rubber handles, mounted on hose terminal part, are available for all the above series. For more information look at page 50.



Atex 94/9

II 3GD c X (only for series 300-350-4430 ABS)

IIB 2GD c T4 T135°C X

USES

