



4804 Coolant Hose



CODAN 4804 RADIATOR HOSE

DESCRIPTION

Black, wrapped coolant hose for coolant and anti-freeze in cars, buses, lorries, tractors, etc. (1102)

Normally installed using hose clamps.

Available in long lengths on request.

Please contact Codan for further information and dimensions.

ADDITIONAL INFORMATION

Type no.	4804
Application	Anti-freeze, Coolant hose, Glycol
Standard length	1 meter
Working temp.	-40°C to 125°C
Inside compound	EPDM
Inside colour	Black
Outside compound	EPDM
Outside colour	Black
Reinforcement	Polyester
Standards	DIN 73411/A 1 and 2:1996
Std. branding	-

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
12,0	19,0	5	15	184	194	4804012000
13,0	20,0	5	15	200	210	4804013000
15,0	22,0	5	15	205	290	4804015000
16,0	23,0	5	15	210	300	4804016000
18,0	25,0	5	15	215	350	4804018000
19,0	27,0	5	15	220	600	4804019000
22,0	30,0	5	15	260	490	4804022000
25,0	33,0	5	15	300	650	4804025000
28,0	36,0	5	15	330	610	4804028000
30,0	38,0	5	15	350	670	4804030000
32,0	40,0	5	15	370	710	4804032000
35,0	43,0	5	15	400	850	4804035000
38,0	46,0	5	15	425	820	4804038000
40,0	48,0	5	15	435	860	4804040000
42,0	50,0	5	15	450	960	4804042000
45,0	53,0	5	15	470	1070	4804045000
48,0	56,0	5	15	500	1200	4804048000
50,0	59,0	5	15	540	1070	4804050000
51,0	61,0	5	15	540	1210	4804051000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.

End of life evaluation for production of Rubber hoses with Textile reinforcement

Inside dia.(mm)	Outside dia.(mm)	Pressure (BAR)	Burst (BAR)	Bend Radius	Weight (g/m)	Product code
55,0	65,0	5	15	850	1200	4804055000
57,0	65,0	5	15	600	1340	4804057000
60,0	69,0	5	15	610	1610	4804060000
63,0	72,0	5	15	620	1480	4804063000
65,0	74,0	5	15	640	1480	4804065000
70,0	80,0	5	15	650	1500	4804070000
76,0	86,0	5	15	660	1760	4804076000
80,0	90,0	5	15	810	2010	4804080000
85,0	97,0	5	15	820	2020	4804085000
90,0	100,0	5	15	850	2100	4804002000
102,0	112,0	5	15	930	2300	4804102000
110,0	120,0	5	15	1000	2500	4804110000
127,0	137,0	5	15	1230	2650	4804127000
152,0	164,0	5	15	1410	3500	4804152000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. The written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care, and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage of vulcanized Rubber Products).

The individual conditions of an application will affect the lifetime of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification. Please contact Codan Rubber for individual product manufacturing tolerances.