



Mutterteil Typ D - MIL A-A-59326A mit BSPP Innengewinde mit NBR Dichtung

Female coupler type D - MIL A-A-59326A with female BSPP thread - NBR gasket
 Coupleur type D taraudé femelle BSPP - MIL A-A-59326A - Joint NBR
 Camlock tipo D: acople hembra - rosca hembra BSPP - Junta NBR
 Kobieta Typ D - MIL A-A-59326A - Gniazdo z gwintem wewnętrznym BSPP - NBR Uszczelka
 Camlock tipo D: versione femmina filettato femmina BSPP - Guarnizione NBR

Part-No.	Material	WP	Dimension	Thread	Price
D050SS2	SS316/CF8M	10 bar	DN15	1/2"	
D075SS	SS316/CF8M	10 bar	DN20	3/4"	
D100SS	SS316/CF8M	10 bar	DN25	1"	
D125SS	SS316/CF8M	10 bar	DN32	1 1/4"	
D150SS	SS316/CF8M	10 bar	DN40	1 1/2"	
D200SS	SS316/CF8M	10 bar	DN50	2"	
D250SS	SS316/CF8M	10 bar	DN65	2 1/2"	
D300SS	SS316/CF8M	10 bar	DN80	3"	
D400SS	SS316/CF8M	7 bar	DN100	4"	
D500SS	SS316/CF8M	5 bar	DN125	5"	
D600SS	SS316/CF8M	5 bar	DN150	6"	



Mutterteil Typ D - MIL A-A-59326A mit BSPP Innengewinde Sicherheitsverschluss System Self-Lock - NBR Dichtung

Female coupler type D - MIL A-A-59326A with female BSPP thread - System Self-Lock - NBR gasket
 Coupleur type D taraudé femelle BSPP - MIL A-A-59326A - Système Self-Lock Joint NBR
 Camlock tipo D - Security: acople hembra - rosca hembra BSPP - Anillas de seguridad - Junta NBR
 Kobieta Typ D - MIL A-A-59326A - Gniazdo z gwintem wewnętrznym BSPP - Samozamykacz systemowy - NBR Uszczelka
 Camlock tipo D - MIL A-A 59326A - versione femmina con filettatura femmina BSPP - Anello di sicurezza autobloccante - Guarnizione NBR

Part-No.	Material	WP	Dimension	Thread	Price
D200SS-SLL	SS316/CF8M	10 bar	DN50	2"	
D300SS-SLL	SS316/CF8M	10 bar	DN80	3"	
D400SS-SLL	SS316/CF8M	7 bar	DN100	4"	

