

PPC Complete Systems for CAN Hydraulic Testers PPC-04-CAN / PPC-PAD-light-CAN



Complete System PPC-PAD-light-CAN-SET (PPC-PAD-light-CAN)



Complete System PPC-04-plus-CAN-SET (PPC-04-plus-CAN)

Order Codes

PPC - PAD-light-CAN-X-SET - T - 160 / 400 / 600 - CAL

① Series and Type

Hydraulic Tester **PPC**

② Version

PPC-04-plus-CAN **04-plus-CAN-SET**
 PPC-PAD-light-CAN **PAD-light-CAN-SET**
 PPC-PAD-light-CAN-AUX **PAD-light-CAN-X-SET**

③ CAN Temperature Sensor

without CAN Temperature Sensor T and SGV (ohne)
 with CAN Temperature Sensor T and SGV **T**

④ Pressure Range and Pressure Sensor

1. CAN Pressure Sensor **see table**

⑤ Pressure Range and Pressure Sensor

2. CAN Pressure Sensor **see table**

⑥ Pressure Range and Pressure Sensor

3. CAN Pressure Sensor **see table**

⑦ Calibration

without calibration certificate (ohne)
 with calibration certificate (factory calibration) **CAL**

Product Description

The PPC complete systems are assembled in different versions according to customer requirements. All complete systems are supplied in a handy case with customised foam inserts and offer space for the components listed below:

Components

Standard Options for Complete Systems PPC-04-plus-CAN

- 1x Case-PPC-04-plus/PAD-light
- 1x Hydraulic Tester PPC-04-plus-CAN
- 1x Power Supply incl. country-specific Adaptor
- Up to 3 CAN Pressure Sensor-PPC-CAN-P with installed Adaptors for STAUFF Test 20 (M16 x 2)
- CAN Temperature Sensor-PPC-CAN-T-M02 with installed SGV-16S-G-W3 (optional)
- Up to 3 CAN Connecting Cables
- Up to 2 CAN Y-Splitter Cables
- 1x CAN Terminating Resistor
- 3x Adaptors SAD for the STAUFF Test 15/12/10 series (standard for all PPC complete systems)
- 1x USB cable 1m (USB A to Micro-USB)
- 1x Quick guide with link to: PC software and instructions

Standard Options for Complete Systems

PPC-PAD-light-CAN or PPC-PAD-light-CAN-AUX

- 1x Case-PPC-04-plus/PAD-light
- 1x Hydraulic Tester PPC-PAD-light-CAN or PPC-PAD-light-CAN-AUX
- 1x Power Supply incl. country-specific Adaptor
- Up to 3 CAN Pressure Sensor-PPC-CAN-P with installed Adaptors for STAUFF Test 20 (M16 x 2)
- CAN Temperature Sensor-PPC-CAN-T-M02 with installed SGV-16S-G-W3 (optional)
- Up to 4 CAN Connecting Cables
- Up to 2 CAN Y-Splitter Cables
- 1x CAN Terminating Resistor
- 3x Adaptors SAD for the STAUFF Test 15/12/10 series (standard for all PPC complete systems)
- 1x USB cable 1m (USB A to C and USB C to C)
- 1x Quick guide with link to: PC software and instructions

Pressure Range and CAN Pressure Sensor

Pressure Range	CAN Pressure Sensor		
000	When ordering a complete system with one or two CAN pressure sensors, specify „000“ for the pressure range of the 2. and / or 3. CAN pressure sensors.		
016	Pressure Range 1. CAN Pressure Sensor	Pressure Range 2. CAN Pressure Sensor	Pressure Range 3. CAN Pressure Sensor
060			
160			
400			
600			
601			
z.B.	016 (16 bar)	060 (60 bar)	000 (0 bar)

Please keep in mind that two CAN pressure sensors with identical measuring ranges are necessary for differential pressure measurements.

Alternative

If you need more space in the case for your components, STAUFF offers the **Case-PPC-PAD-plus** as an alternative. This can hold several measuring devices at the same time and offers a variety of storage options (at least 9 pressure sensors and 2 flow turbines and much more). The case is only available individually. The contents must be ordered separately.

