

## ROHRBOGEN - SCHLAUCHNIPPEL

**Type 8044.90**

90° gebogen, mit Dichtkegel nach DIN 3863 und Überwurfmutter BSP

### **BENT TUBE WITH HOSE NIPPLE**

90° bent with conical nipple according to DIN 3863 and swivel nut BSP



DN (NW)	für Schlauch-Innen-Ø for hose inside Ø  mm	L 1 mm	L 2 mm	Überwurfmutter Gewinde swivel nut thread	Bestell-Nr. part-no.
3	4 - 5	34	25	G 1/8"	8044.90.0300
6	7 - 8	39	30	G 1/4"	8044.90.0600
6/4	5 - 6	34	25	G 1/4"	8044.90.0604
8	9 - 10	39	30	G 3/8"	8044.90.0800
13	14 - 15	48	50	G 1/2"	8044.90.1300
13/10	11 - 12	44	35	G 1/2"	8044.90.1310
20/16	17 - 18	50	55	G 3/4"	8044.90.2016
25/20	21 - 22	60	55	G 1"	8044.90.2520


## AUßENGEWINDE - SCHLAUCHNIPPEL

**Type 8050**

metrisch, 60° Innen-Konus, passend für Schlauchnippel nach DIN 3863, Type 8010

### **NIPPLE WITH OUTSIDE THREAD**

metric, 60° inner cone, fits hose nipples according to DIN 3863, type 8010



DN (NW)	für Schlauch-Innen-Ø for hose inside Ø  mm	SW mm	Gewinde thread	L 1 mm	L 2 mm	Bestell-Nr. part-no
3	4 - 5	11	M 10 x 1	12	8	8050.0300
4	5 - 6	12	M 12 x 1,5	14	10	8050.0400
6	7 - 8	14	M 14 x 1,5	15	10	8050.0600
8	9 - 10	17	M 16 x 1,5	16	11	8050.19.080051
10	11 - 12	19	M 18 x 1,5	16	11	8050.1000
10/8	9 - 10	19	M 18 x 1,5	16	11	8050.1008
13	14 - 15	22	M 22 x 1,5	18	12	8050.1300
16	17 - 18	27	M 26 x 1,5	22	12	8050.1600
20	21 - 22	30	M 30 x 1,5	24	14	8050.2000