



Versatile hose designed for both discharge and suction applications involving hot water and coolant. Also suitable for handling light chemicals. Can be used as a radiator hose. **EHW** has both a tube and cover made of EPDM rubber with a reinforcement of high-tensile synthetic textile and steel helical wire. Highly flexible and easy to handle, ensuring smooth installation even in tight spaces. Outer rubber layer is weather-resistant. Excellent pressure resistance and high wear durability. Operating temperature -40°C to +125°C. Supplied in 61 meter coils, delivered on pallet.

Application Areas: Construction, industrial, marine and automotive.

| item number | ID | YD | operating pressure | min. burst pressure | min. bend radius | vacuum | weight | length |
|-------------|-------|-----|--------------------|---------------------|------------------|--------|--------|--------|
| | mm | mm | bar | bar | mm | bar | kg/m | m |
| EHW024-08 | 12.7 | 22 | 10.0 | 30 | 45 | - 0.92 | 0.37 | 61 |
| EHW024-10 | 16.0 | 25 | 10.0 | 30 | 55 | - 0.92 | 0.45 | 61 |
| EHW024-12 | 19.0 | 28 | 10.0 | 30 | 65 | - 0.92 | 0.51 | 61 |
| EHW024-14 | 22.0 | 31 | 10.0 | 30 | 75 | - 0.92 | 0.56 | 61 |
| EHW024-16 | 25.4 | 34 | 10.0 | 30 | 90 | - 0.92 | 0.61 | 61 |
| EHW024-20 | 31.8 | 42 | 10.0 | 30 | 110 | - 0.92 | 0.96 | 61 |
| EHW024-24 | 38.1 | 48 | 10.0 | 30 | 135 | - 0.92 | 1.13 | 61 |
| EHW024-32 | 50.8 | 62 | 10.0 | 30 | 200 | - 0.92 | 1.69 | 61 |
| EHW024-40 | 63.5 | 75 | 10.0 | 30 | 270 | - 0.92 | 2.07 | 61 |
| EHW024-48 | 76.2 | 89 | 10.0 | 30 | 340 | - 0.92 | 2.82 | 61 |
| EHW024-64 | 101.6 | 115 | 10.0 | 30 | 450 | - 0.92 | 3.80 | 61 |