



## Blanking Plug with 24° Taper / O-Ring (DKO) Type FI-VD ▪ Series L / S



### Ordering Codes

#### \*FI-VD\*-15\*L\*-V\*-W3\*-M

|                                                                         |                                                                                |
|-------------------------------------------------------------------------|--------------------------------------------------------------------------------|
| * Blanking Plug with 24° Taper / O-Ring (DKO)                           | <b>FI-VD</b>                                                                   |
| * Outside Tube Diameter D1 (in mm)                                      | <b>-15</b>                                                                     |
| * Series                                                                | Light Series <b>L</b><br>Heavy Series <b>S</b>                                 |
| * Seal Material                                                         | FKM (Viton®) <b>-V</b><br>EPDM <b>-E</b>                                       |
| * Material Code                                                         | Steel, zinc/nickel-plated <b>-W3</b>                                           |
| Please contact STAUFF for alternative materials and surface finishings. |                                                                                |
| * Assembling / Kitting                                                  | Blanking plug only <b>—</b><br>Blanking plug supplied with union nut <b>-M</b> |

### Connecting Parts



Union Nut  
Type **FI-M**

Page 33

### Spare Parts / Accessories



O-Ring  
Type **O-RING**

Page 239

| Series | Tube OD<br>(mm/in)<br>D1 | PN<br>(bar/psi) | Dimensions<br>(mm/in)<br>L1 <sup>1</sup> S1 |      | Weight<br>(kg/lbs) ca.<br>per 100 | Ordering Codes <sup>3</sup> |
|--------|--------------------------|-----------------|---------------------------------------------|------|-----------------------------------|-----------------------------|
| L      | 6                        | 800             | 17                                          | 14   | 0,55                              | FI-VD-06L/S-V-W3            |
|        | .24                      | 11600           | .67                                         | .55  | 1.21                              |                             |
|        | 8                        | 800             | 17                                          | 17   | 0,91                              | FI-VD-08L/S-V-W3            |
|        | .31                      | 11600           | .67                                         | .67  | 2.02                              |                             |
|        | 10                       | 800             | 20                                          | 19   | 1,55                              | FI-VD-10L/S-V-W3            |
|        | .39                      | 11600           | .79                                         | .75  | 3.41                              |                             |
|        | 12                       | 630             | 21                                          | 22   | 2,23                              | FI-VD-12L/S-V-W3            |
|        | .47                      | 9135            | .83                                         | .87  | 4.91                              |                             |
|        | 15                       | 400             | 20                                          | 27   | 3,60                              | FI-VD-15L-V-W3              |
|        | .59                      | 5800            | .79                                         | 1.06 | 7.92                              |                             |
|        | 18                       | 400             | 21                                          | 32   | 4,88                              | FI-VD-18L-V-W3              |
|        | .71                      | 5800            | .83                                         | 1.26 | 10.74                             |                             |
|        | 22                       | 250             | 23                                          | 36   | 7,70                              | FI-VD-22L-V-W3              |
|        | .87                      | 3625            | .91                                         | 1.42 | 16.94                             |                             |
|        | 28                       | 250             | 23                                          | 41   | 12,00                             | FI-VD-28L-V-W3              |
|        | 1.10                     | 3625            | .91                                         | 1.61 | 26.40                             |                             |
|        | 35                       | 250             | 29                                          | 50   | 24,00                             | FI-VD-35L-V-W3              |
|        | 1.38                     | 3625            | 1.14                                        | 1.97 | 52.80                             |                             |
|        | 42                       | 250             | 30                                          | 60   | 35,00                             | FI-VD-42L-V-W3              |
|        | 1.65                     | 3625            | 1.18                                        | 2.36 | 77.00                             |                             |
| S      | 6                        | 800             | 17                                          | 17   | 0,55                              | FI-VD-06L/S-V-W3            |
|        | .24                      | 11600           | .67                                         | .67  | 1.21                              |                             |
|        | 8                        | 800             | 17                                          | 19   | 0,91                              | FI-VD-08L/S-V-W3            |
|        | .31                      | 11600           | .67                                         | .75  | 20.01                             |                             |
|        | 10                       | 800             | 20                                          | 22   | 1,55                              | FI-VD-10L/S-V-W3            |
|        | .39                      | 11600           | .79                                         | .87  | 3.41                              |                             |
|        | 12                       | 630             | 21                                          | 24   | 2,23                              | FI-VD-12L/S-V-W3            |
|        | .47                      | 9135            | .83                                         | .94  | 4.91                              |                             |
|        | 14                       | 630             | 23                                          | 27   | 3,30                              | FI-VD-14S-V-W3              |
|        | .55                      | 9135            | .91                                         | 1.06 | 7.26                              |                             |
|        | 16                       | 630             | 24                                          | 30   | 4,30                              | FI-VD-16S-V-W3              |
|        | .63                      | 9135            | .94                                         | 1.18 | 9.46                              |                             |
|        | 20                       | 420             | 28                                          | 36   | 8,10                              | FI-VD-20S-V-W3              |
|        | .79                      | 6091            | 1.10                                        | 1.42 | 17.82                             |                             |
|        | 25                       | 420             | 31                                          | 46   | 13,50                             | FI-VD-25S-V-W3              |
|        | .98                      | 6091            | 1.22                                        | 1.81 | 29.70                             |                             |
|        | 30                       | 420             | 34                                          | 50   | 21,20                             | FI-VD-30S-V-W3              |
|        | 1.18                     | 6091            | 1.34                                        | 1.97 | 46.64                             |                             |
|        | 38                       | 420             | 38                                          | 60   | 36,90                             | FI-VD-38S-V-W3              |
|        | 1.50                     | 6091            | 1.50                                        | 2.36 | 81.18                             |                             |

<sup>1</sup> Approximate dimension in assembled condition.

<sup>2</sup> Weight excluding union nut.

<sup>3</sup> Standard scope of delivery: Blanking plug only.

Standard seal material is FKM (Viton®).

