



KF – Flanged male coupling

- Galvanized steel, Some sizes electro-galvanized steel (ELF).
- Stainless steel EN 1.4404 / AISI 316L. Lock, ring and hook-system made of EN 1.4301 / AISI 304.
- Stainless steel EN 1.4404 / AISI 316L. Lock, ring and hook-system made of EN 1.4301 / AISI 304.

	Galvanized steel	Stainless steel	Stainless steel/silumin		
Size	Art.no.	Art.no.	Art.no.	L (mm)	W (kg)
48 x DN40	1622018 (ELF)	1632009	1631902	105	2,2
48 x DN50	1622026 (ELF)	1632017	1631910	105	2,9
76 x DN50	1622059 (ELF)	1632025	1631928	120	3,3
76 x DN65	1622067 (ELF)	1632033	1631936	120	3,7
76 x DN 80 Styrstos	1622073 (ELF)	1632040	-	145	4,5
76 x DN80	1622075	1632041	1631944	120	4,4
102 x DN80	1622081 (ELF)	1632055	-	140	5,5
102 x DN100 Styrstos	1622082 (ELF)	1632057	-	160	5,7
102 x DN100	1622083	1632058	1631951	135	5,5
133 x DN125	1622091	1632066	1631958	145	7,5
152 x DN150	1622109	1632074	1631966	145	10,0
204 x DN200 PN10	1622120	1632082	-	200	20,0



KE – Flanged female coupling

- Galvanized steel, Some sizes electro-galvanized steel (ELF). Lock, ring and hook-system made of galvanized steel. Flange DIN PN10/16
- Stainless steel EN 1.4404 / AISI 316L. Lock, ring and hook-system made of EN 1.4301 / AISI 304. Flange of EN 1.4404 / AISI 316L, DIN PN 10/16
- Stainless steel EN 1.4404 / AISI 316L. Lock, ring and hook-system made of EN 1.4301 / AISI 304. Flange of silumin DIN PN10

Standard EPDM rubber seal included.

	Galvanized steel	Stainless steel	Stainless steel/silumin		
Size	Art.no.	Art.no.	Art.no.	L (mm)	W (kg)
48 x DN50	1622224 (ELF)	1630813	1630714	290	4,1
76 x DN50	1622257 (ELF)	1630821	1630730	310	5,2
76 x DN65	1622265 (ELF)	1630839	1630748	310	6,5
76 x DN80	1622273	1630847	1630755	310	7,0
102 x DN100	1622281	1630854	1630763	325	8,2
133 x DN125	1622299 (ELF)	1630862	-	410	14,0
152 x DN150	1622307	1630870	1630779	410	17,0
204 x DN200 PN10	1622320	-	-	500	25,0



KXV – Blind male coupling

- Galvanized steel.
- Stainless steel EN 1.4404 / AISI 316L.

	Galvanized steel	Stainless steel		
Size	Art.no.	Art.no.	L (mm)	Wikt (kg)
38	-	1630902	30	0,2
48	1622414	1630904	37	0,3
76	1622430	1630912	50	0,5
102	1622448	1630920	45	0,7
133	1622455	1630928	50	1,1
152	1622463	1630936	65	1,8
204	1622475	1630944	110	6,6



KXM – Blind female coupling

- Galvanized steel. Lock, ring and hook-system made of galvanized steel.
- Stainless steel EN 1.4404 / AISI 316L. Lock, ring and hook-system made of EN 1.4301 / AISI 304.

Standard EPDM rubber seal included.

	Galvanized steel	Stainless steel		
Size	Art.no.	Art.no.	L (mm)	W (kg)
38	-	1630977	60	0,4
48	1622513	1630979	80	1,2
76	1622539	1630987	90	2,3
102	1622547	1630995	95	3,2
133	1622554	1630997	120	5,5
152	1622562	1630999	130	8,0
204	1622575	1631000	120	12,9

* = Price on demand.

■ = Not in stock - delivery time 2-3 weeks.

All measurements and weights are valid for couplings made of galvanized steel.