

B

Clamp Body ▪ Profiled Design

Profiled Inside Surface with Tension Clearance





Ordering Codes

Clamp Body ***3*006-*PP**

One clamp body is consisting of two clamp halves.

* 1st part of STAUFF Group	**3**
* Exact outside diameter Ø D1 (mm)	**006**
* Material code (see below)	**PP**

Standard Materials

Polypropylene
Colour: Green
Material code: **PP**

Polypropylene
Colour: Black
Material code: **PP-BK**

Polyamide
Colour: Black
Material code: **PA**

Thermoplastic Elastomer (87 Shore-A)
Colour: Black
Material code: **SA87**

Aluminium
Colour: Self-Colour
Material code: **AL**

See pages 178 / 179 for material properties and technical information.

Special Materials

Please contact STAUFF for further details on fire-proof clamp body materials, tested and approved according to several international fire-protection standards (such as BS 6853, EN 45545-2, UL 94 and many more).

See pages 180 / 181 for material properties and technical information.

Product Features

- Proven, tested and trusted product in various markets
- Recommended for the safe installation of rigid pipes and tubes
- Available for all commonly used pipe and tube outside diameters
- Environmental protection due to vibration/noise reducing design
- Excellent weathering resistance, even under extreme conditions

Group STAUFF	Group DIN	Outside Diameter Pipe / Tube Ø D1 (mm)	Outside Diameter Pipe / Tube Ø D1 (in)	Nominal Bore Pipe (in)	Nominal Bore Copper Tube ASTM B88 (in)	Ordering Codes (2 Clamp Halves) (** = Material)	Dimensions (mm/in) L1 PP/PA/SA	L1 AL	L2	H	S min.	Width
3S	1	6				3006-**						
		6,4	1/4			3006.4-**						
		8	5/16			3008-**						
		9,5	3/8		1/4	3009.5-**						
		10		1/8		3010-**						
		12				3012-**						
		12,7	1/2		3/8	3012.7-**	55	56	33	32	0,6	30,5
		13,5		1/4		3013.5-**	2.16	2.20	1.30	1.26	.02	1.20
		14				3014-**						
		15				3015-**						
		16	5/8		1/2	3016-**						
		17,2		3/8		3017.2-**						
		18				3018-**						
		20				3020-**						
4S	2	19	3/4			4019-**						
		20				4020-**						
		21,3		1/2		4021.3-**						
		22	7/8		3/4	4022-**						
		25				4025-**	70	70	45	48	0,6	30,5
		25,4	1			4025.4-**	2.76	2.76	1.77	1.89	.02	1.20
		26,9		3/4		4026.9-**						
		28				4028-**						
		30				4030-**						
5S	3	30				5030-**						
		32	1-1/4			5032-**						
		33,7		1		5033.7-**						
		35			1-1/4	5035-**	85	85	60	60	0,6	30.5
		38	1-1/2			5038-**	3.35	3.35	2.36	2.36	.02	1.20
		40				5040-**						
		41,3			1-1/2	5041.3-**						
		42		1-1/4		5042-**						
6S	4	38	1-1/2			6038-**						
		42		1-1/4		6042-**						
		44,5	1-3/4			6044.5-**						
		48,3		1-1/2		6048.3-**						
		50,8	2			6050.8-**						
		54			2	6054-**						
		55				6055-**	115	120	90	89	2	45
		57				6057-**	4.53	4.72	3.54	3.50	.08	1.77
		57,2	2-1/4			6057.2-**						
		60,3		2		6060.3-**						
		63,5	2-1/2			6063.5-**						
		65				6065-**						
		70	2-3/4			6070-**						

See page 39 for STAUFF Group 7S to 12S (DIN Group 5 to 10).

Additional outside diameters are available upon request. Please contact STAUFF for further information.