

CAM & GROOVE SEALS



SQUARE SEAL - FPM

ND	Inch	OD Ø +/- 0.3 mm	ID Ø +/- 0.2 mm	Height +/- 0.2 mm	Weight/pc Kg	Reference
15	1/2"	26.5	17.5	4.0	0.002	VLXV013
20	3/4"	35.0	22.0	5.5	0.005	VLXV019
25	1"	40.0	27.0	6.4	0.007	VLXV025
32	1.1/4"	50.0	35.0	6.4	0.009	VLXV032
40	1.1/2"	56.0	41.0	6.4	0.010	VLXV038
50	2"	67.0	51.0	6.4	0.010	VLXV050
65	2.1/2"	80.0	60.0	6.4	0.020	VLXV063
80	3"	95.0	76.0	6.4	0.020	VLXV075
100	4"	124.0	102.0	6.4	0.030	VLXV100
125	5"	150.5	124.0	6.4	0.050	VLXV125
150	6"	180.0	153.0	6.4	0.060	VLXV150



Material: FPM

Colour: Green

Dimensions in compliance with EN 14420-7 / FED MIL A-A59326A, with exception of ND 15,
ND 125, ND 150 and ND 200 See chapter F for more information regarding chemical resistance

SQUARE SEAL - CSM

ND	Inch	OD Ø +/- 0.3 mm	ID Ø +/- 0.2 mm	Height +/- 0.2 mm	Weight/pc Kg	Reference
15	1/2"	26.5	17.5	4.0	0.002	VLXH013
20	3/4"	35.0	22.0	5.5	0.005	VLXH019
25	1"	40.0	27.0	6.4	0.007	VLXH025
32	1.1/4"	50.0	35.0	6.4	0.009	VLXH032
40	1.1/2"	56.0	41.0	6.4	0.010	VLXH038
50	2"	67.0	51.0	6.4	0.010	VLXH050
65	2.1/2"	80.0	60.0	6.4	0.020	VLXH063
80	3"	95.0	76.0	6.4	0.020	VLXH075
100	4"	124.0	102.0	6.4	0.030	VLXH100
125	5"	150.5	124.0	6.4	0.050	VLXH125
150	6"	180.0	153.0	6.4	0.060	VLXH150



Material: CSM

Colour: Black green marked

Dimensions in compliance with EN 14420-7 / FED MIL A-A59326A, with exception of ND 15,
ND 125, ND 150 and ND 200 See chapter F for more information regarding chemical resistance