

ENTLÜFTUNGSSCHLAUCH

Type 2110

ohne Umflechtung, Ausführung A DIN 73379 (Stand 8/52)

VENT HOSE without braiding, type A DIN 73379 (edition 8/52)



DN (NW)	d ± 0,4 mm	D ± 0,5 mm	Für drucklosen Einsatz als Entlüftungsschlauch. For the use without pressure as a vent hose.	Bestell-Nr. part-no.
2	3,5	7,5		2110.0200-20
3	4,5	8,5		2110.0300-20
4	5,4	9,4		2110.0400-20
6	7,2	11,2		2110.0600-20
8	9,5	14,0		2110.0800-20
10	11,0	16,5		2110.1000-20
13	14,5	20,5		2110.1300-20
16	18,0	25,0		2110.1600-20
20	22,0	31,0		2110.2000-20

Auch mit Umflechtung aus Edelstahldraht lieferbar. Die Bestell-Nr. ist dann 2110.01.xxxx.

Also available with stainless steel wire braiding. The order-no. changes to 2110.01.xxxx.

KRAFTSTOFFSCHLAUCH

Type 2120

mit verzinkter Stahldrahtumflechtung, Ausführung C DIN 73379 (Stand 8/52)

FUEL HOSE with zinc plated steel wire braiding type C DIN 73379 (edition 8/52)



DN (NW)	d + 0,3 - 0,5 mm	D ± 0,6 mm	Betriebs- druck working pressure bar	Prüf- druck testing pressure bar	Berst- druck bursting pressure bar	kleinster zulässiger Biegeradius smallest ben- ding radius mm	Bestell-Nr. part-no.
2	3,5	8,5	32	48	80	25	2120.0200
3	4,5	9,5	30	45	75	25	2120.0300
4	5,5	10,5	30	45	75	25	2120.0400
6	7,5	12,5	24	36	60	30	2120.0600
8	9,5	15,0	20	30	50	40	2120.0800
10	11,0	17,5	20	30	50	45	2120.1000
13	14,0	21,5	18	27	45	50	2120.1300
16	17,5	26,0	14	21	35	70	2120.1600
20	20,5	32,0	14	21	35	90	2120.2000
25	24,0	35,0	12	20	35	150	2120.2500