



Feuerschutzschlauch - EN45545 / DIN5510-2

Fire protection hose - EN45545 / DIN5510-2

Tuyau de protection contre l'incendie - EN45545 / DIN5510-2

Funda de protección contra incendios - EN45545 / DIN5510-2

Wąż przeciwpożarowy - EN45545 / DIN5510-2

Protezione antifuoco per tubi - EN45545 / DIN5510-2

Beschreibung:	Silikonbeschichtetes Fiberglas
Betriebstemperatur:	max 260°C kurzfristig 1100°C
Norm:	EN45545 und DIN5510-2 UL 1441
Rollenware:	<= DN75 20m > DN75 15m (kein Anschnitt)
Desription:	Silicone coated fiberglas
Temperature:	max 260°C short time 1100°C
Norm:	EN45545 and DIN5510-2 UL 1441
Coil:	<= DN75 20m > DN75 15m (no short lengths available)

Part-No.	 mm	 mm	 bar	 mm	 %	 g/m	Price/m
SSCF-6	6	8,4					
SSCF-8	8	10,6					
SSCF-10	10	13,2					
SSCF-12	12	15,4					
SSCF-13	13	16,8					
SSCF-15	15	19,2					
SSCF-20	20	24,6					
SSCF-22	22	27					
SSCF-25	25	30,2					
SSCF-30	30	35,8					
SSCF-32	32	38					
SSCF-35	35	41,2					
SSCF-38	38	44,6					
SSCF-40	40	46,8					
SSCF-45	45	52					
SSCF-50	50	57,4					
SSCF-55	55	62,8					
SSCF-60	60	68					
SSCF-65	65	73,2					
SSCF-70	70	78,6					
SSCF-75	75	83,8					
SSCF-89	89	99					
SSCF-102	102	114					
SSCF-105	105	117					
SSCF-110	110	122					
SSCF-115	115	127					
SSCF-127	127	139					