

**Description**

**Item No.**

**Waste Oil Collecting Funnel, ø 400 / 560 mm**

designed to fit to container with R2" drum adaptor  
 metal funnel ø 400 mm  
 ø 560 mm plastic top with insert mesh  
 750 mm pipe length with ball valve  
 R2" bung adapter vertical individually adjustable

Waste Oil Collecting Funnel, 400 / 560 mm

35 549 58



**Plastic Funnel with Flap Lid**

plastic funnel with stainless steel strainer and lockable flap lid, suitable for waste oil and chemical disposal

material: PP  
 diameter: 250 mm  
 Thread: R2" and 2" TriSure, male

Funnel FSC-PP-250

33 517 00



**Liquid Extraction and Transfer Unit, stationary**

The extraction and discharge unit with 6 l capacity is suitable for fluids such as oil, diesel, emulsions, water, coolants and other non-aggressive fluids.  
 Not suitable for liquids with A1 flash point < 21° C (gasoline, aviation fuel, etc.).

**Accessories:**

- 1.5 m suction and discharge hose with ball valve and snap-on connector for suction probes
- 2 flexible suction probes 6 and 8 mm diameter, 680 mm long (suction probe connection Ø 16 mm)

for more suction probes and suction adaptors please see accessories for waste oil pumps

Liquid extraction and discharge unit 6 l stationary

35 554 12



**Liquid Extraction and Transfer Unit, mobile**

The extraction and discharge unit with 18 l capacity is suitable for fluids such as oil, diesel, emulsions, water, coolants and other non-aggressive fluids.  
 Not suitable for liquids with A1 flash point < 21° C (gasoline, aviation fuel, etc.).

**Accessories:**

- 1.5 m suction and discharge hose with ball valve and snap-on connector for suction probes
- 2 flexible suction probes 6 and 8 mm diameter, 680 mm long (suction probe connection Ø 16 mm)

for more suction probes and suction adaptors please see accessories for waste oil pumps

Liquid extraction and discharge unit 18 l mobile

35 554 43

