

1:1

# PUR Hose Kits – with Series 310

ISO 6150 B, A-A 59439

- Series 310 couplings and nipples
- Flexible PUR hose with long service life
- Pre-assembled and ready to use

CEJN Hose Kits come pre-assembled and ready for immediate use. They consist of an extremely flexible, straight braided or spiral polyurethane (PUR) hose combined with Series 310 Standard or eSafe couplings and nipples with reusable Stream-Line connections.

PUR Hose Kits are also available with Series 300, 320 and 410 Standard or Vented Safety couplings and nipples.



Flow capacity is measured at 100 PSI (6.9 bar) inlet pressure, and pressure drop at 6 PSI (0.4 bar).

		Service length	Part No.	ID x OD	Max working pressure	
<b>SERIES 310</b>	Spiral	6.6 °F (2.0 m)	19 958 9923	(5 x 8 mm)	145 PSI (10 bar)	
			19 958 9927	(6.5 x 10 mm)	145 PSI (10 bar)	
			19 958 9931	(8 x 12 mm)	145 PSI (10 bar)	
		13.1 °F (4.0 m)	19 958 9928	(6.5 x 10 mm)	145 PSI (10 bar)	
			19 958 9932	(8 x 12 mm)	145 PSI (10 bar)	
			19 958 9936	(11 x 16 mm)	145 PSI (10 bar)	
	Straight Braided	19.7 °F (6.0 m)	19 958 9929	(6.5 x 10 mm)	145 PSI (10 bar)	
			19 958 9933	(8 x 12 mm)	145 PSI (10 bar)	
			19 958 9930	(6.5 x 10 mm)	145 PSI (10 bar)	
		26.2 °F (8.0 m)	19 958 9934	(8 x 12 mm)	145 PSI (10 bar)	
			19 958 9832	(8 x 12 mm)	232 PSI (16 bar)	
			19 958 9337	(9.5 x 13.5 mm)	232 PSI (16 bar)	
49.2 °F (15.0 m)	19 958 9833	(8 x 12 mm)	232 PSI (16 bar)			
	19 958 9338	(9.5 x 13.5 mm)	232 PSI (16 bar)			
	<b>SERIES 310, ESAFE</b>	Spiral	6.6 °F (2.0 m)	19 958 9331	(8 x 12 mm)	145 PSI (10 bar)
19 958 9709				(8 x 12 mm)	145 PSI (10 bar)	
19 958 9710				(8 x 12 mm)	145 PSI (10 bar)	
Straight Braided		26.2 °F (8.0 m)	19 958 9711	(8 x 12 mm)	145 PSI (10 bar)	
			32.8 °F (10.0 m)	19 958 9701	(8 x 12 mm)	232 PSI (16 bar)
			49.2 °F (15.0 m)	19 958 9702	(8 x 12 mm)	232 PSI (16 bar)



CEJN reserves the right to make changes without further notification. Thread connections are listed according to ISO Standards. Other connections and sealing material on request. Check with an authorized CEJN distributor for availability and prices. Some part numbers may be subject to minimum order quantities. Please visit our website, [www.cejn.com](http://www.cejn.com), for general maintenance tips.

## AIR FLOW

- HOSE 5X8 MM
- HOSE 6.5X10 MM
- HOSE 8X12 MM
- HOSE 9.5X13.5 MM
- HOSE 11X16 MM

