

## P/N 0E33/2611NHHV2

Diaphragm pump in aluminum series AB-1 with membranes in NBR, balls and seats in Hytrel®

### SECTORS OF USE

Agriculture, Automotive, Building and road construction, Industry, Mining, Lube trucks and transports

### FEATURES

|                                         |                                            |
|-----------------------------------------|--------------------------------------------|
| Ratio                                   | 1:1                                        |
| Flow rate                               | 170 l/min                                  |
| Compatible fluids                       | water, mineral-vegetable oils, diesel fuel |
| Pump material                           | aluminum                                   |
| Ball valve material                     | Hytrel®                                    |
| Air inlet connection                    | G 3/8" (f)                                 |
| Fluid inlet-outlet connection           | G 1.1/4" (f) x G 1" (f)                    |
| Air working pressure                    | 2÷6 bar                                    |
| Max supply pressure                     | 8 bar                                      |
| Average air consumption                 | 1200 l/min                                 |
| Noise level                             | 75 dB                                      |
| Fluid temperature                       | -10÷+90 °C                                 |
| Max solids diameter                     | ø 3 mm                                     |
| Suitable for drums or tank              | -                                          |
| Suction-delivery ball valve with spring | ball valve with spring                     |



|         |                  |
|---------|------------------|
| Packing | No. 1 - 0,025 m³ |
| Weight  | 14 kg            |