



P/N OE39610 *

Pulser meter for oil with inlet/outlet G 1/2" (f) is used to measure fluids and to transmit data. It is usually installed on centralized system to control and manage delivery of fluids.



P/N OE39611 *

Pulser meter for antifreeze and windshield washer fluid with inlet/outlet G 1/2" (f). It is used to measure fluids and to transmit data. It is usually installed on centralized system to control and manage delivery of fluids.



P/N OE39613 *

Pulser meter for oil with inlet/outlet G 3/4" (f). It is used to measure fluids and to transmit data. It is usually installed on centralized system to control and manage delivery of fluids.



P/N OE39614 *

Pulser meter for diesel with inlet/outlet G 3/4" (f). It is used to measure fluids and to transmit data. It is usually installed on centralized system to control and manage delivery of fluids.



P/N OE39615 *

Pulser meter for oil with inlet/outlet G 1" (f). It is usually installed on centralized system to control and manage delivery of fluids.



P/N OE39616 *

Pulser meter for diesel with inlet/outlet G 1" (f). It is usually installed on centralized system to control and manage delivery of fluids.



P/N OE39609 *

AISI 304 stainless steel pulser for AdBlue® with inlet/outlet G 1/2" (f). Used for fluid measurement and remote data transmission. They are usually installed in fixed systems for fluid transfer/distribution where centralized control and management systems operate.