

For the SWIVELLING version add the suffix "/SO" at the P/N.
For example: 300/80/SO

FIXED PAINTED STEEL



Supplied with:

- NBR orange hose Standard EN ISO 3821 with brass coupling
- brass swivel joint
- Viton® seals
- central shaft in galvanized steel
- inlet hose 1,5 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	Hose supplied	Connection	
			Inlet	Outlet
S. 300	300/80	without hose	M 3/8"G LH	M 3/8"G LH
	300/81	8m 8x15 (949/8)	F 3/8"G LH	F 3/8"G LH
	300/82	10m 10x17 (959/10)	F 3/8"G LH	F 3/8"G LH
S. 350	350/80	without hose	M 3/8"G LH	M 3/8"G LH
	350/81	15m 8x15 (949/15)	F 3/8"G LH	F 3/8"G LH
	350/82	15m 10x17 (959/15)	F 3/8"G LH	F 3/8"G LH
S. 430	430/80	without hose	M 3/8"G LH	M 3/8"G LH
	430/82	20m 8x15 (949/20)	F 3/8"G LH	F 3/8"G LH
	430/84	18m 10x17 (959/18)	F 3/8"G LH	F 3/8"G LH
S. 530	530/80	without hose	M 3/8"G LH	M 3/8"G LH
	530/82	28m 8x15 (949/28)	F 3/8"G LH	F 3/8"G LH
	530/84	27m 10x17 (959/27)	F 3/8"G LH	F 3/8"G LH
S. 540	540/80	without hose	M 3/8"G LH	M 3/8"G LH
	540/82	30m 10x17 (959/30)	F 3/8"G LH	F 3/8"G LH

L-H: left hand thread



Atex 94/9 ▶ II 3GD c (T5) T100°C X

Suction waste oil

For the SWIVELLING version add the suffix "/SO" at the P/N.
For example: 430/40/AS/SO

FIXED PAINTED STEEL



FIXED PAINTED STEEL



Supplied with:

- hose in black synthetic rubber with galvanized steel coupling
- brass swivel joint
- Viton® seals
- inlet hose 2 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	P/N	Hose supplied	Connection	
				Inlet	Outlet
S. 430	430/40/AS	-	without hose	F 1/2"G	F 3/8"G
	430/41/AS	-	10m 1/2" (963/11)	F 1/2"G	M 1/2"G
	430/415/AS	-	without hose	F 1/2"G	F 1/2"G
S. 4430 ABS	4430/40/AS	-	without hose	F 1/2"G	F 3/8"G
S. 440 enclosed	-	440/41/AS	10m 1/2" (963/11)	F 1/2"G	M 1/2"G



Atex 94/9 ▶ IIB 2GD c T4 T135°C X
▶ II 3GD c X (only for series 4430 ABS)