



This clamp is manufactured in AISI 430 with an additional matt-black surface treatment which increases its corrosion resistance. Thanks to the surface treatment, this clamp can be mounted discreetly in any application, making it a favourite in automotive or motorcycle applications.

The geometry, band, stamping, housing and screw are identical to other ASFA clamps, meaning that the performance is not altered in any way.

DIN 3017. The Black ASFA LW3 hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

**MATERIAL:** Stainless steel band and housing W3 AISI 430 X6Cr17 (DIN 1.4016)  
Stainless steel W4 AISI 304 Cu screw

**FINISH:** Black - Delta Seal

**CORROSION RESISTANCE:** 250 hours Salt Spray (ASTM B-117)

Part Number	Ø Application mm	A +0.3 -0.2	L +1 -0.5	S ±0.1	H Max.	B Max.	Maximum Values		Box Quantity	Outer Box Quantity
							Pressure (Bar)	Par (Nm)		
73016011	8-16	9	22,1	0,65	10,5	14	45	3,0	200	800
73016020	12-22	9	22,1	0,65	10,5	14	45	3,0	200	800
73016038	16-27	9	23,6	0,75	10,5	14	42	3,5	200	800
73016046	20-32	9	23,6	0,75	10,5	14	36	3,5	200	800
73016062	25-40	9	25,6	0,75	10,5	14	32	4,0	100	800
73016070	30-45	9	25,6	0,75	10,5	14	28	4,0	100	800
73016089	32-50	9	25,6	0,75	10,5	14	24	4,0	100	800
73016095	40-60	9	25,6	0,75	10,5	14	19	4,0	100	400
73016100	50-70	9	29,6	0,75	10,5	14	17	4,0	100	100
73016118	60-80	9	29,6	0,75	10,5	14	15	4,0	100	100
73016126	70-90	9	29,6	0,75	10,5	14	13	4,0	50	400
73016134	80-100	9	29,6	0,75	10,5	14	11	4,0	50	50
73016142	90-110	9	29,6	0,75	10,5	14	11	4,0	25	200
73016150	100-120	9	29,6	0,75	10,5	14	11	4,0	25	200
73016169	110-130	9	29,6	0,75	10,5	14	11	4,0	25	25
73016177	120-140	9	29,6	0,75	10,5	14	11	4,0	25	200
73016185	130-150	9	29,6	0,75	10,5	14	11	4,0	25	25
73016193	140-160	9	29,6	0,75	10,5	14	11	4,0	25	25