


37° - FLARED TUBE CONNECTORS

102078

Connector male JIC - Metric with elastomer seal ISO 9974 ports



T		RIFERIMENTO REFERENCE	J	F	A	B	D	CH
MM.	IN.							
6	1/4	A102078-0610	7/16-20 UNF-2A	M10x1-6g	30	14	8	14
6	1/4	A102078-0612	7/16-20 UNF-2A	M12x1,5-6g	35	14	12	17
8	5/16	A102078-0810	1/2-20 UNF-2A	M10x1-6g	30	14	8	14
8	5/16	A102078-0812	1/2-20 UNF-2A	M12x1,5-6g	35	14	12	17
10	3/8	A102078-1014	9/16-18 UNF-2A	M14x1,5-6g	36	14	12	19
10	3/8	A102078-1016	9/16-18 UNF-2A	M16x1,5-6g	36	14	12	22
12	1/2	A102078-1216	3/4-16 UNF-2A	M16x1,5-6g	39	17	12	22
12	1/2	A102078-1218	3/4-16 UNF-2A	M18x1,5-6g	39,5	17	12	24
14÷16	5/8	A102078-1618	7/8-14 UNF-2A	M18x1,5-6g	42	19,5	12	24
14÷16	5/8	A102078-1620	7/8-14 UNF-2A	M20x1,5-6g	45	19,5	14	27
14÷16	5/8	A102078-1622	7/8-14 UNF-2A	M22x1,5-6g	45	19,5	14	27
18-20	3/4	A102078-2022	1"1/16-12 UN-2A	M22x1,5-6g	48,5	22	14	30
18-20	3/4	A102078-2027	1"1/16-12 UN-2A	M27x2-6g	52	22	16	32
25	1"	A102078-2526	1"5/16-12 UN-2A	M26x1,5-6g	55	23	16	36
25	1"	A102078-2527	1"5/16-12 UN-2A	M27x2-6g	53	23	16	36
25	1"	A102078-2533	1"5/16-12 UN-2A	M33x2-6g	56	23	18	41
30-32	1"1/4	A102078-3242	1"5/8-12 UN-2A	M42x2-6g	61	24,5	20	50
38	1"1/2	A102078-3848	1"7/8-12 UN-2A	M48x2-6g	68	27,5	22	55
12	1/2	SA102078-1214	3/4-16 UNF-2A	M14x1,5-6g	39	17	12	22

FOR S.P.A. - NORME E DIMENSIONI SOGGETTE A MODIFICHE SENZA PREAVVISO.
FOR S.P.A. - DESIGN DETAILS AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.