


Blanking Screw for Ports (Heavy Duty) Type FI-VSV-...-R-WD



Whitworth Parallel Pipe Thread (BSPP)

Profile Sealing Ring

Ordering Codes		PN bar	Dimensions mm					Torque N·m	Weight kg ca. per 100	Ordering Codes
FI-VSV-R*1/2*-WD*-B*-W3			Thread T	D1	i	L1	S1	S2		
* Blanking Screw for Ports	FI-VSV	400	G 1/8	14	8	18	5	14	18	1,56 FI-VSV-R1/8-WD-B-W3
* Thread Type Whitworth Parallel Pipe Thread (BSPP)	R	400	G 1/4	19	12	20	6	19	33	2,73 FI-VSV-R1/4-WD-B-W3
* Thread Size acc. to dimension table	1/2	400	G 3/8	22	12	22	8	22	70	4,48 FI-VSV-R3/8-WD-B-W3
Please always indicate thread sizes, e.g. 1/2!		400	G 1/2	27	14	24	10	27	90	7,27 FI-VSV-R1/2-WD-B-W3
* Seal Type Profile Sealing Ring	-WD	400	G 3/4	32	16	28	12	32	181	13,02 FI-VSV-R3/4-WD-B-W3
* Seal Material NBR (Buna-N®) FKM (Viton®)	-B	400	G 1	39,9	18	33	17	41	250	23,80 FI-VSV-R1-WD-B-W3
* Material Code Steel, zinc/nickel-plated	-V	400	G 1 1/4	49,9	20	38	22	50	400	42,00 FI-VSV-R1-1/4-WD-B-W3
Please contact STAUFF for alternative materials and surface finishings.		400	G 1 1/2	54,9	22	40	24	55	500	55,60 FI-VSV-R1-1/2-WD-B-W3

Standard seal material is NBR (Buna-N®).

Male stud acc. to ISO 1179-2 (Type E)
Port acc. to ISO 1179-1

Male threaded studs were designed for female threaded ports in components made of steel. For applications with components made of softer mating materials (e.g. Aluminum), the use of connectors with additionally rolled male threads is recommended.

Torque recommendations with a tolerance of +10% and refer to original components from the STAUFF Connect product range made of steel with zinc/nickel coating and apply for Steel mating material.

Please contact STAUFF prior to the assembly for further information.

Spare Parts / Accessories

Profile Sealing Ring
Type WDG

Page 238