



P/N	Number of conductors	Type of cable	Cable length	Max. charging current*	Weight
<b>OE2155</b>	6 red + 6 black	12 x 1,5 - H05 VV-F	4 + 2 m	30 A	7,6 Kg
<b>OE2156</b>	6 red + 6 black	12 x 1,5 - H05 VV-F	7 + 2 m	30 A	8,5 Kg

\* with unwound cable



### SPEED CONTROL

The versions listed below come with clutch so that cable rewinding can be performed at a controlled speed.

They are marked by the SPEED CONTROL dataplate.

P/N	Number of conductors	Type of cable	Cable length	Max. charging current*	Weight
<b>OE2155F</b>	6 red + 6 black	12 x 1,5 - H05 VV-F	4 + 2 m	30 A	8,0 Kg
<b>OE2156F</b>	6 red + 6 black	12 x 1,5 - H05 VV-F	7 + 2 m	30 A	8,9 Kg

\* with unwound cable

## Related products

With plug and Schuko socket

P/N	Type of cable	Cable length
<b>OE2315S</b>	3G x 1,5 H05 VV-F	14 + 1 m



With plug and Schuko socket and Speed Control

P/N	Type of cable	Cable length
<b>OE2315SF</b>	3G x 1,5 H05 VV-F	14 + 1 m

With LED lamp

P/N	Type of cable	Cable length
<b>OE2210L</b>	3G x 1,5 H05 VV-F	14 + 1 m



With LED lamp and Speed Control

P/N	Type of cable	Cable length
<b>OE2210LF</b>	3G x 1,5 H05 VV-F	14 + 1 m

## Accessory

**P/N 260/03**

**Bayonet bracket**, lets you easily move the tape reel within the various workstations.



## Examples of cable reels with accessories

