



Flachdichtringe Form A nach DIN 7603

Werkstoff: SF-Cu, auf eine Härte von max. 45 HB weichgeglüht

Betriebstemperatur: nach DIN max. +300° C

flat sealing rings form A according to DIN 7603

material: SF-Cu, on a hardness annealed by 45 HB max

working temperature: according to DIN max. +300° C

Abmessungen dimensions	Art.-Nr.
4X8X1	100 501
5X9X1	100 503
5X11X1	100 504
6X10X1	100 505
6X12X1	100 506
7,4X12X1	100 700
8X11,5X1	190 506
8X12X1	100 514
8X12X1,5	100 515
8X14X1	100 517
8X14X1,5	100 518
8X14X2	100 519
10X14X1	100 531
10X14X1,5	100 532
10X14X2	100 533
10X16X1	100 536
10X16X1,5	100 537
10X16X2	100 538
10X18X1	100 540
10X18X1,5	100 541
10X19X2	100 543
12X16X1	100 547
12X16X1,5	100 548
12X17X1,5	100 551
12X18X1	100 553
12X18X1,5	100 554
12X18X2	100 555
12X20X2	100 558
13X18X1	100 562
13X18X1,5	100 563
13X18X2	100 564
14X18X1	100 567
14X18X1,5	100 568
14X18X2	100 569
14X20X1	100 571
14X20X1,5	100 572
14X20X2	100 573
14X21X1,5	100 574
14X22X1,5	100 576
15X20X1,5	100 580
15X21X1,5	100 581
15X24X1,5	100 582
16X19,5X1	130 156
16X20X1,5	100 585
16X22X1	100 587
16X22X1,5	100 588
16X24,5X1,5	100 590
17X21X1,5	100 591
17X23X1,5	100 593

Abmessungen dimensions	Art.-Nr.
18X22X1,5	100 597
18X24X1,5	100 601
18X24X2	100 602
20X24X1,5	100 608
20X26X1,5	100 610
20X26X2	100 611
20X28X1,5	100 612
21X26X1,5	100 616
21X27X1,5	100 619
21X28X1,5	100 621
22X26X1,5	100 624
22X27X1,5	100 627
22X27X2	100 628
22X28X1,5	100 629
22X28X2	100 630
22X29X1,5	100 631
24X28X1,5	100 639
24X29X2	100 641
24X30X2	100 643
24X32X2	100 644
26,1X29X1	130 157
26X31X2	100 648
26X32X2	100 651
26X34X2	100 652
27X32X2	100 656
27X34X2	100 658
28X36X2	100 659
30X36X2	100 662
30X38X2	100 663
32X38X2	100 664
33X39X2	100 668
33X41X2	100 670
34X40X2	100 671
35X41X2	100 672
36X42X2	100 673
36X44X2	100 674
38X44X2	100 677
40X47X2	100 680
42X49X2	100 683
45X52X2	100 687
48X55X2	100 690
50X57X2	100 691
52X60X2,5	100 692
56X64X2,5	100 693
60X68X2,5	100 695
64X72X2,5	100 694

Auch im Sortiment lieferbar.
Also available in the assortment.

Kupfer-Dichtringe

copper sealing rings

Form C nach DIN 7603

Werkstoff: SF-Cu, als 0,3 mm dicke Ummantelung und einem astbestfreien Füllstoff aus hochtemperaturbeständigen, mineralischen und keramischen Fasern

Betriebstemperatur: nach DIN max. +250° C

form C according to DIN 7603

material: SF-Cu, as 0,3 mm thick sheathing and a asbestos-free filler from high temperature resistant, mineral and ceramic fiber

working temperature: according to DIN max. +250° C

Abmessungen dimensions	Art.-Nr.
6X10X1,5	100 302
8X12X1,5	100 305
8X14X1,5	100 306
10X16X1,5	100 308
12X6X2	100 309
12X18X2	100 310
14X20X2	100 313
16X20X2	100 316
16X22X2	100 317
16X24X2	100 318
17X23X2	100 321
18X24X2	100 320
20X26X2	100 324
21X26X2	100 325
22X29X2	100 327

Abmessungen dimensions	Art.-Nr.
24X32X2,5	100 330
26X32X2,5	100 331
27X32X2,5	100 334
28X36X2,5	100 336
30X36X2,5	100 337
33X39X2,5	100 340
35X41X2,5	100 341
36X42X2,5	100 342
38X44X2,5	100 344
40X47X2,5	100 345
42X49X2,5	100 346
45X52X2,5	100 348
48X55X2,5	100 349
52X60X3	100 352
60X68X3	100 353

Auch im Sortiment lieferbar.
Also available in the assortment.



Kupfer-Dichtringe Zwilling

copper sealing twin rings

Zur Montage von 2 Dichtringen gleichzeitig unter schwierigen Bedingungen

Werkstoff: SF-Cu, Zwillingsringe bestehen aus 2 Dichtringen der Form A, die durch einen Steg miteinander verbunden sind

Betriebstemperatur: nach DIN max. +300° C

for the assembly of 2 sealing rings at the same time under difficult conditions

material: SF-Cu, twin rings consist of 2 sealing rings of the form A, which are connected by a bar

working temperature: according to DIN max. +300° C

Abmessungen dimensions	Abstand/mm distance/mm	Art.-Nr.
6X11X1 Ku-ZW	8	100 805
8X12X1 Ku-ZW	8	100 801
8X12X1 Ku-ZW	13	100 802
14X20X1,5 Ku-ZW	14	100 806

