


CONFIGURATION

L	Control	Standard Screw Adjustment
S	Adjustment Range	25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar) Standard Setting
N	Seal Material	Buna-N
(none)	Material/Coating	

Normally closed, direct-acting, 3-way directional cartridges are switching devices typically used in moderate flow circuits. They can be used by themselves or to actuate larger pilot-operated directional cartridges or logic cartridges. The valve shifts when the pressure differential between port 1 and port 4 exceeds the setting.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-21A
Series	1
Capacity	7 gpm
Maximum Operating Pressure	5000 psi
Factory Pressure Settings Established at	4 gpm
Maximum Valve Leakage at 110 SUS (24 cSt)	2 in ³ /min.
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	7/8 in.
Valve Installation Torque	30 - 35 lbf ft
Adjustment Screw Internal Hex Size	5/32 in.
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990021007
Seal kit - Cartridge	Polyurethane: 990021002
Seal kit - Cartridge	Viton: 990021006
Model Weight	0.40 lb.

NOTES For Series 1 cartridges configured with an O control (panel mount handknob), a .75 in. (19 mm) diameter hole is required in the panel.


CONFIGURATION OPTIONS
Model Code Example: DRBNArray

CONTROL	(L)	ADJUSTMENT RANGE	(S)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment	S	25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar)	N	Buna-N		Standard Material/Coating
C Tamper Resistant - Factory Set		Standard Setting	V	Viton		/AP Stainless Steel, Passivated
K Handknob	A	500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar)				/LH Mild Steel, Zinc-Nickel
O Handknob with Panel Mount		Standard Setting				
	B	50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)				
	D	Standard Setting				
	E	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)				
	W	Standard Setting				
		2500 - 4500 psi (175 - 315 bar), 1000 psi (70 bar)				

TECHNICAL FEATURES

- Port 3 can be used as a work port.
- The flow path between port 2 and port 3 is bidirectional.
- Because of their direct-acting design, these cartridges feature low internal leakage and low pilot flow consumption.
- Direct-acting and pilot-operated versions of these valves are interchangeable. They fit the same cavities and have the same flow paths.
- Pressure at port 4 is directly additive to the setting of the valve.
- This valve is not bistable; it is capable of modulating between the two positions shown.
- Maximum pressure at port 3 should be limited to 3000 psi (210 bar). This is due to fatigue strength limits not hydraulic operating limits.
- Incorporates the Sun floating-style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES



RELATED MODELS

- [DRBNX](#) 2-way, direct-acting, fixed setting, directional valve with drain to port 4 - normally closed