

LIGHT RANGE 304 Stainless Steel



| Part No. | Adjustment mm | Band Width mm | Band Thickness mm | Recommended Torque Nm | Maximum Torque Nm | Maximum Pressure PSI | Part No. |
|----------|---------------|---------------|-------------------|-----------------------|-------------------|----------------------|----------|
| 000SS | 9.5-12 | 9.3 | 0.7 | 3.4 | 4.5 | 203 | 000SS |
| M00SS | 11-16 | 9.3 | 0.7 | 3.4 | 4.5 | 203 | M00SS |
| O0SS | 13-20 | 9.3 | 0.7 | 3.4 | 4.5 | 203 | O0SS |
| LR022SS | 12-22 | 9.3 | 0.7 | 3.4 | 4.5 | 182 | LR022SS |
| LR027SS | 16-27 | 9.3 | 0.7 | 3.4 | 4.5 | 182 | LR027SS |
| LR032SS | 20-32 | 9.3 | 0.7 | 3.4 | 4.5 | 92 | LR032SS |
| LR040SS | 25-40 | 9.3 | 0.7 | 4.5 | 6.0 | 92 | LR040SS |
| LR045SS | 30-45 | 9.3 | 0.7 | 4.5 | 6.0 | 92 | LR045SS |
| LR050SS | 32-50 | 9.3 | 0.7 | 4.5 | 6.0 | 92 | LR050SS |
| LR060SS | 40-60 | 9.3 | 0.7 | 4.5 | 6.0 | 92 | LR060SS |
| LR070SS | 50-70 | 9.3 | 0.7 | 4.5 | 6.0 | 92 | LR070SS |
| LR080SS | 60-80 | 9.3 | 0.7 | 4.5 | 6.0 | 39 | LR080SS |
| LR090SS | 70-90 | 9.3 | 0.7 | 4.5 | 6.0 | 39 | LR090SS |
| LR100SS | 80-100 | 9.3 | 0.7 | 4.5 | 6.0 | 39 | LR100SS |
| LR110SS | 90-110 | 9.3 | 0.7 | 4.5 | 6.0 | 39 | LR110SS |
| LR120SS | 100-120 | 9.3 | 0.7 | 4.5 | 6.0 | 39 | LR120SS |
| LR130SS | 110-130 | 9.3 | 0.7 | 4.5 | 6.0 | 39 | LR130SS |
| LR140SS | 120-140 | 9.3 | 0.7 | 4.5 | 6.0 | 39 | LR140SS |
| LR150SS | 130-150 | 9.3 | 0.7 | 4.5 | 6.0 | 17 | LR150SS |
| LR160SS | 140-160 | 9.3 | 0.7 | 4.5 | 6.0 | 17 | LR160SS |

Quality Assurance



SAE J1508 Surface Vehicle Standards-Hose Clamp Specifications, Type FE is referenced in the quality control methods for the design/manufacture of Lightweight Range Jubilee Clips.

Corrosion Resistance

1000 hours NSS Test

Fastening

7mm A/F screw

Industry Recommendations



304 Stainless Steel