



Support Sleeve for 37° Flared Tube Fittings Type FI-BH ■ Series L / S



B

Series	Tube OD	PN	Dimensions			Weight kg ca. per 100	Ordering Codes
	mm	bar	mm	D3	L1		
L	6	500	7,6	10,2	10	0,21	FI-BH-06L/S-W3
	8	500	9,3	12,2	11	0,25	FI-BH-08L/S-W3
	10	500	11,5	14,2	12	0,37	FI-BH-10L/S-W3
	12	400	13,6	16,2	12,5	0,46	FI-BH-12L/S-W3
	15	400	17,5	20,2	13,5	0,89	FI-BH-15L-W3
	18	400	21	24,2	14	1,40	FI-BH-18L-W3
	22	250	24,2	27,8	17,5	1,59	FI-BH-22L-W3
	28	250	30,2	33,8	16,5	1,99	FI-BH-28L-W3
	35	250	38	42,7	18,5	3,70	FI-BH-35L-W3
	42	250	45	49,7	20,5	4,94	FI-BH-42L-W3
S	6	630	7,6	10,2	10	0,21	FI-BH-06L/S-W3
	8	630	9,3	12,2	11	0,25	FI-BH-08L/S-W3
	10	630	11,5	14,2	12	0,37	FI-BH-10L/S-W3
	12	630	13,6	16,2	12,5	0,46	FI-BH-12L/S-W3
	14	630	17,5	20,2	14	1,20	FI-BH-14S-W3
	16	630	18,5	22	16,5	1,25	FI-BH-16S-W3
	20	400	24,2	27,8	17	2,39	FI-BH-20S-W3
	25	400	28,5	32,8	19,5	2,98	FI-BH-25S-W3
	30	400	34	39	21	4,50	FI-BH-30S-W3
	38	400	42	48,5	26	7,34	FI-BH-38S-W3

Ordering Codes

FI-BH-15*L*-W3

* Support Sleeve for 37° Flared Tube Fittings **FI-BH**

* Outside Tube Diameter D1 (in mm) **-15**

* Series Light Series **L**
Heavy Series **S**

* Material Code Steel, zinc/nickel-plated **-W3**

Please contact STAUFF for alternative materials and surface finishings.

Support Sleeve: DIN 3949