

INDUSTRIAL HOSE WATER & AIR // MULTIPURPOSE

THE WORLD OF HOSE

ESSENTIAL™ WATER MASTER SD



								
mm	mm	mm	MPa	MPa	mm	kg/100m	m	REF.
25	35	5.0	1.0	3.0	125	70	40	WATER MAS SD 25mm x CL40
25	35	5.0	1.0	3.0	125	70	61*	WATER MAS SD 25mm x CL61
32	42	5.0	1.0	3.0	160	90	40	WATER MAS SD 32mm x CL40
32	42	5.0	1.0	3.0	160	90	61*	WATER MAS SD 32mm x CL61
38	48	5.0	1.0	3.0	190	110	40	WATER MAS SD 38mm x CL40
38	48	5.0	1.0	3.0	190	110	61*	WATER MAS SD 38mm x CL61
51	63	6.0	1.0	3.0	255	160	40	WATER MAS SD 51mm x CL40
51	63	6.0	1.0	3.0	255	160	61*	WATER MAS SD 51mm x CL61
63	76	6.5	1.0	3.0	315	230	40	WATER MAS SD 63mm x CL40
63	76	6.5	1.0	3.0	315	230	61*	WATER MAS SD 63mm x CL61
76	89	6.5	1.0	3.0	380	280	40	WATER MAS SD 76mm x CL40
76	89	6.5	1.0	3.0	380	280	61*	WATER MAS SD 76mm x CL61
102	116	7.0	1.0	3.0	510	390	40	WATER MAS SD 102mm x CL40
102	116	7.0	1.0	3.0	510	390	61*	WATER MAS SD 102mm x CL61
127	142	7.5	1.0	3.0	635	570	40	WATER MAS SD 127mm x CL40
152	169	8.5	1.0	3.0	760	800	40	WATER MAS SD 152mm x CL40
203	224	10.5	1.0	3.0	1015	1290	40	WATER MAS SD 203mm x CL40

* 61 m coils are made to order ** Vacuum resistance up to -0.9 bar

RECOMMENDED FOR

Vacuum and pressure hose (SD) for water, waste water, sea water, mud, slurry. Water suction in heavy duty service requiring a compact, rugged and light weight hose.

TUBE

Black EPDM, smooth.

REINFORCEMENT

Synthetic, high tensile textile with steel wire helix.

COVER

EPDM rubber, black, good weather and aging resistance.

TEMPERATURE RANGE

-35°C to +95°C.

BURST PRESSURE

> 30 bar.

BRANDING TRANSFER LABEL

ESSENTIAL™ WATER MASTER SD - 10 BAR