

Grease 400 - 600 bar

For the SWIVELLING version add the suffix "/SO" at the P/N.
For example: 300/51/SO

FIXED PAINTED STEEL



FIXED S. STEEL AISI 304



Supplied with:

- hose in black synthetic rubber with galvanized steel coupling
- swivel joint in galvanized steel or s. steel AISI 304
- Polyurethane seals
- central shaft in galvanized steel or stainless steel AISI 304
- inlet hose 0,6 m to connect the hose reel to the system (standard on the versions with hose)



| | | P/N | P/N | Hose supplied | Connection | |
|---------|-------------|---------|---------|-------------------|------------|---------|
| | | | | | Inlet | Outlet |
| 400 bar | S. 300 | 300/50 | 302/50 | without hose | F 3/8"G | F 3/8"G |
| | | 300/51 | 302/51 | 12m 1/4" (935/12) | F 3/8"G | M 1/4"G |
| | S. 350 | 350/50 | 352/50 | without hose | F 3/8"G | F 3/8"G |
| | | 350/51 | 352/51 | 12m 1/4" (935/12) | F 3/8"G | M 1/4"G |
| | | 350/52 | 352/52 | 16m 1/4" (935/16) | F 3/8"G | M 1/4"G |
| | S. 430 | 430/50 | 432/50 | without hose | F 3/8"G | F 1/2"G |
| | | 430/51 | 432/51 | 12m 1/4" (935/13) | F 3/8"G | M 1/4"G |
| | | 430/52 | 432/52 | 18m 1/4" (935/18) | F 3/8"G | M 1/4"G |
| | | 430/55 | 432/55 | 10m 3/8" (957/10) | F 3/8"G | M 1/4"G |
| | | 430/56 | 432/56 | 15m 3/8" (957/15) | F 3/8"G | M 1/4"G |
| | S. 4430 ABS | 4430/50 | 4432/50 | without hose | F 3/8"G | F 1/2"G |
| | | 4430/51 | 4432/51 | 12m 1/4" (935/13) | F 3/8"G | M 1/4"G |
| | | 4430/52 | 4432/52 | 18m 1/4" (935/18) | F 3/8"G | M 1/4"G |
| | | 4430/55 | 4432/55 | 10m 3/8" (957/10) | F 3/8"G | M 1/4"G |
| | | 4430/56 | 4432/56 | 15m 3/8" (957/15) | F 3/8"G | M 1/4"G |
| | S. 530 | 530/50 | 532/50 | without hose | F 3/8"G | F 1/2"G |
| | | 530/51 | 532/51 | 20m 3/8" (957/20) | F 3/8"G | M 1/4"G |
| | | 530/52 | 532/52 | 25m 3/8" (957/25) | F 3/8"G | M 1/4"G |
| | S. 540 | 540/50 | 542/50 | without hose | F 3/8"G | F 1/2"G |
| | | 540/51 | 542/51 | 30m 3/8" (957/30) | F 3/8"G | M 1/4"G |



Atex 94/9

- ▶ II 3GD c X (only for series 300-350-4430 ABS)
- ▶ IIB 2GD c T4 T135°C X

USES

