



PVEA32-ACTUATOR--S7-1x4AMP-H-PAS

11166855 [↗](#)

Model code: SVSELEC112UR0002CCBBA4007I0P7706050000000E0008900C01200227

Where to buy [↗](#)

Product specifications

Characteristic	Value	Description
Pilot Pressure	1	13.5 (PVE)
Voltage	1	11-32
Connector Type	2	1x4 AMP JPT SAAB
Connector Direction	U	90 (Up)
Control Signal	R	Ratiometric
CAN Protocol	0	N/A
Digital Type	0	N/A
Float Direction	0	N/A
Hysteresis	2	2.0%
On-Stroke Response A	C	350 ms
On-Stroke Response B	C	350 ms
De-Stroke Reaction A	B	225 ms
De-Stroke Reaction B	B	225 ms
Resolution	A	50
Max Oil Consumption	0	0 l/min
Max Oil Consump. Steady State	0	0 l/min
Fault Reaction & Recovery	I	Indication Only
Output Signal	0	N/A
Disable Function	P	Power Save
Nominel A Stroke	7	7
Nominel B Stroke	7	7



Characteristic	Value	Description
Minimum Float Position	0	N/A
IP Rating	6	IP66
Manual Override	0	N/A
Coil Power	5	5 W
Port Connection Type	0	N/A
A Port Placement	0	N/A
B Port Placement	0	N/A
Extra Function	0	N/A
Valve Side Interface	0E	PVE32 O-Ring
Outward Side Interface	00	N/A
Length	089	89
Pilot Pressure Neutral	0	N/A
Pilot Pressure Full Stroke	0	N/A
Maximum System Pressure Peaks	C	60
Primer	0	N/A
Product Category	1	Standard Part
Marking	2	CE EAC
Ex Application	0	N/A
Certification	CS	ISO13849 Compliant
PVDI connector coding	0	N/A
Marking	2	CE EAC
Port Size	00	N/A
Product Type		N/A
Voltage	1	11-32



General specifications

Characteristic	Value
Proposition 65	Cancer and Reproductive Harm

For the most current information and other product assets, please use this link to visit the product page on PowerSource [↗](#)