

PPC Starter System ■ Type PPC-PAD-plus

B



Content of the case may vary



Trolley is optionally available (Trolley-Frame-Case-PPC-PAD-plus)

Product Description

An initial starter kit with hydraulic tester, different input modules, cables and accessories is also available in a case. This contains everything required for the preferred sensor connection variant. This means that cables for connecting 4 CAN bus sensors or 3/6 analogue sensors as well as the required input modules are included. Sensors and test couplings are not included and have to be ordered separately.

The case is robust, lightweight and contains two special foam inserts that protect the device and any accessories in a well structured storage solution.

The sets are available with a device with or without WIFI capability and can also be purchased as a calibrated version with certificate.

Individual Components

Delivery standard for complete system SET-PPC-PAD-plus

- PPC-PAD-plus
- 24 V DC/2.5 A power supply unit incl. country-specific adaptor
- USB 2.0 cable (2 m/6.56 ft)
- Quickguide with Link for PC-Software and Manual
- Case-PPC-PAD-plus

And the following equipment, depending on the set:

SET-PPC-PAD-plus-ANALOG-3

- 1 analogue input module
- 3 analogue cables, 3 m

SET-PPC-PAD-plus-ANALOG-6

- 2 analogue input modules
- 6 analogue cables, 3 m

SET-PPC-PAD-plus-CAN-4

- 2 CAN cables, 0.5 m
- 2 CAN cables, 2 m
- 2 Y-splitters
- 2 terminating resistors

Order Codes

SET-PPC-PAD-plus - W - ANALOG-6 - CAL

①

②

③

④

① Series and Type

Hydraulic Tester	SET-PPC-PAD-plus
------------------	------------------

② WIFI

Without WIFI	(none)
With WIFI	W

③ Version

for 3 analogue STAUFF Sensors	ANALOG-3
for 6 analogue STAUFF Sensors	ANALOG-6
for 4 STAUFF CAN Sensors	CAN-4

④ Calibration

Without calibration certificate	(none)
With calibration certificate (factory calibration)	CAL

Ordering table for measuring and test instruments

This list shows the individual components for the PPC-04-plus, PPC-06-plus, PPC-08-plus and PPC-PAD-plus Hydraulic Testers with their exact Order Codess.

* Pressure spikes up to 1000 bar/14500 psi

Description	Order Codes
1. Hydraulic Tester PPC-04-plus	
Hydraulic Tester PPC-04-plus with 2 sensor inputs, including accessories	PPC-04-plus
Hydraulic Tester PPC-04-plus with 2 sensor inputs, including accessories, calibrated	PPC-04-plus-CAL
CAN Hydraulic Tester PPC-04-plus-CAN with one CAN bus interface, including accessories	PPC-04-plus-CAN
Power Supply Unit (110/230 V AC) for PPC-04-plus with USB connection, including country-specific adaptor	Power-supply-PPC-04-plus-110/230V-USB
Case-PPC-04-plus/PAD-light (with foam insert)	Case-PPC-04-plus/PAD-light
2. Hydraulic Tester PPC-PAD-light	
Hydraulic Tester PPC-PAD-light for up to 4 sensor inputs, including accessories	PPC-PAD-light
Hydraulic Tester PPC-PAD-light for up to 4 sensor inputs, including accessories	PPC-PAD-light-CAL
Hydraulic Tester PPC-PAD-light-CAN for up to 6 CAN interfaces, including accessories	PPC-PAD-light-CAN
Hydraulic Tester PPC-PAD-light-CAN-AUX for up to 6 CAN interfaces, Third-party Sensors, including accessories	PPC-PAD-light-CAN-AUX
Quick Charger	Power-Supply-PPC-PAD-light-MULTI
Case-PPC-04-plus/PAD-light (with foam insert)	Case-PPC-04-plus/PAD-light
3. Hydraulic Tester PPC-PAD-plus	
Hydraulic Tester PPC-PAD-plus for up to 48 STAUFF CAN interfaces, including accessories	PPC-PAD-plus
Hydraulic Tester PPC-PAD-plus for up to 48 STAUFF CAN interfaces, including accessories, calibrated	PPC-PAD-plus-CAL
Hydraulic Tester PPC-PAD-plus for up to 48 STAUFF CAN interfaces, including accessories, WIFI capability	PPC-PAD-plus-W
Hydraulic Tester PPC-PAD-plus für bis zu 48 STAUFF CAN interfaces, including accessories, WIFI capability, calibrated	PPC-PAD-plus-W-CAL
Analogue Input Module	INPUT-MODUL-ANALOG-PPC-PAD-plus
Analogue Input Module, calibrated	INPUT-MODUL-ANALOG-PPC-PAD-plus-CAL
Analogue Input Module, galvanically isolated sensor inputs	INPUT-MODUL-ANALOG-PPC-PAD-plus-GALV
Analogue Input Module, galvanically isolated sensor inputs, calibrated	INPUT-MODUL-ANALOG-PPC-PAD-plus-GALV-CAL
CAN Input Module	INPUT-MODUL-CAN-PPC-PAD-plus
Connector for third-party sensor inputs M12 5-pin	PLUG-PPC-PAD-plus-AUX-M12A/5
Carrying Strap	Carry-strap-PPC-PAD-plus
Power Supply Unit (110/230 V AC) for PPC-PAD-plus, including country-specific adaptor	Power-Supply-PPC-PAD-plus-MULTI
Case-PPC-PAD-plus (with foam insert)	Case-PPC-PAD-plus
Trolley	Trolley-Frame-Case-PPC-PAD-plus
4. Current/Voltage/Frequency Converter/Third-Party Sensors	
Current/Voltage/Frequency Converter/Third-Party Sensors (up to 4 A DC/48 V DC)	Sensorkonverter-PPC
5. Cables	
Analogue	
Connection Cable 3 m/9.84 ft (5-pin connection on both ends)	Cable-PPC-04/12-3
Extension Cable 5 m/16.40 ft (5-pin connection on both ends)	Cable-PPC-04/12-5-EXT
CAN	
CAN Connection Cable 0.5 m/1.64 ft	Cable-PPC-CAN0.5
CAN Connection Cable 2 m/6.65 ft	Cable-PPC-CAN2
CAN Connection Cable 5 m/16.40 ft	Cable-PPC-CAN5
CAN Connection Cable 10 m/32.81 ft	Cable-PPC-CAN10
CAN Y-Splitter Cable 0.3 m/0.98 ft	Cable-PPC-CAN-Y
CAN Terminating Resistor	Resistor-PPC-CAN