

TW - Kupplung Typ VK mit BSPP Innengewinde PFA ausgekleidet

Male adapter type VK BSPP female thread - PFA coated

Raccord type VK taraudé femelle BSPP - Revêtu de PFA

TW- Racor macho tipo VK con rosca hembra BSPP- Recubierto de PFA

TW Wtyk typ VK z gwintem wewnętrznym BSPP - Z powłoką PFA

Raccordo maschio tipo VK filettato femmina BSPP - Rivestimento in PFA

NEW

Part-No.	Material	WP	Shank	Thread	Price
2VKSPFA-W	SS 1.4408	25 bar	DN50	G2"	
3VKSPFA-W	SS 1.4408	25 bar	DN80	G3"	
4VKSPFA-W	SS 1.4408	25 bar	DN100	G4"	
2VKSPFA-B	SS 1.4408 PFA black coated	25 bar	DN50	G2"	
3VKSPFA-B	SS 1.4408 PFA black coated	25 bar	DN80	G3"	
4VKSPFA-B	SS 1.4408 PFA black coated	25 bar	DN100	G4"	




CONDUCTIVE
TW - Kappe Typ MB ohne Kette

CSM Dichtung

Cap MB for VK without chain - CSM gasket

Bouchon MB pour raccord VK - Joint CSM

TW- Tapa hembra tipo MB para VK sin cadena - Junta CSM

TW Pokrywa typ MB do VK bez łańcuszka - Uszczelka CSM

TW - Tappo MB per VK senza catena - Guarnizione CSM



Part-No.	Material	WP	Dimension	Price
2MBS	SS 1.4408	16 bar	DN50	
3MBS	SS 1.4408	16 bar	DN80	
4MBS	SS 1.4408	16 bar	DN100	

