



## NYLON (SLEEVE HOOK AND LOOP)

**TEXWRAP** is a foldable sleeve made of polyamide fibers coated on one side with UV-resistant PU. The exclusive locking system, made of highly resistant VCO (Velcro) allows to obtain a tubular protection of endless length and easy to assemble.

**TEXWRAP** can be supplied in customized versions: cut to size and stitched, with the addition of eyelets and locking catch to improve tear resistance.

**Standard colour:** Black  
Other colours are available on request

**Temperature range:**

-40° C to +180° C  
(-40° F to +356° F)

- MSHA approval for mining applications n. IC207/02
- Volume resistivity (applied voltage 500V)  $\Omega \cdot m$   $5.9 \cdot 10^{12}$  according to CEI 15-23
- Surface resistivity (applied voltage 500V)  $\Omega$   $1.4 \cdot 10^{16}$  according to CEI 15-23

**TEXWRAP** is available in the following range:

Part Nr.	Round diameter [mm]	Coil length [m]	Quantity per box [m]	Availability
<b>TEXW03516A4</b>	35	50	150	Stock
<b>TEXW04016A4</b>	40	50	150	Stock
<b>TEXW05016A4</b>	50	50	150	Stock
<b>TEXW06016A4</b>	60	50	100	Stock
<b>TEXW07516A4</b>	75	50	100	Stock
<b>TEXW08016A4</b>	80	50	100	Stock
<b>TEXW10016A4</b>	100	50	50	Stock
<b>TEXW12516A4</b>	125	50	50	Stock
<b>TEXW15016A4</b>	150	50	50	Stock
<b>TEXW17516A4</b>	175	50	50	Stock
<b>TEXW20016A4</b>	200	50	50	Stock

Rolls of 50 m



*Example of customized version with eyelets*