

Mutterteil Typ B - MIL A-A-59326A mit BSPT Außengewinde mit NBR Dichtung

Female coupler type B - MIL A-A-59326A with male BSPT thread - NBR gasket

Coupleur type B fileté mâle BSPT - MIL A-A-59326A - Joint NBR

Camlock tipo B: acople hembra - rosca macho BSPT Junta NBR

Kobieta Typ B - MIL A-A-59326A - Gniazdo z gwintem zewnętrznym BSPT - NBR Uszczelka

Camlock tipo B: versione femmina filettata maschio BSPT - Guarnizione NBR



Part-No.	Material	WP	Dimension	Thread	Price
B050AL	Aluminum	10 bar	DN15	1/2"	
B075AL	Aluminum	10 bar	DN20	3/4"	
B100AL	Aluminum	10 bar	DN25	1"	
B125AL	Aluminum	10 bar	DN32	1 1/4"	
B150AL	Aluminum	10 bar	DN40	1 1/2"	
B200AL	Aluminum	10 bar	DN50	2"	
B250AL	Aluminum	10 bar	DN65	2 1/2"	
B300AL	Aluminum	10 bar	DN80	3"	
B400AL	Aluminum	7 bar	DN100	4"	
B500AL	Aluminum	5 bar	DN125	5"	
B600AL	Aluminum	5 bar	DN150	6"	
B800AL	Aluminum	4 bar	DN200	8"	

Mutterteil Typ B - MIL A-A-59326A mit BSPT Außengewinde

Vakuum Einsatz - mit NBR Dichtung

Female coupler type B - MIL A-A-59326A with male BSPT thread - using vacuum - NBR gasket

Coupleur type B fileté mâle BSPT - MIL A-A-59326A - utilisation sous vide - Joint NBR

Camlock tipo B: acople hembra - rosca macho BSPT - para vacío - Junta NBR

Kobieta Typ B - MIL A-A-59326A - Gniazdo z gwintem zewnętrznym BSPT - dla próżni - NBR Uszczelka

Camlock tipo B: versione femmina filettata maschio BSPT - per il vuoto - Guarnizione NBR



NEW

Part-No.	Material	WP	Dimension	Thread	Price
B150AL-V	Aluminum	17 bar	DN40	1 1/2"	
B200AL-V	Aluminum	17 bar	DN50	2"	
B250AL-V	Aluminum	10 bar	DN65	2 1/2"	
B300AL-V	Aluminum	8,5 bar	DN80	3"	
B400AL-V	Aluminum	6,5 bar	DN100	4"	

