
Hexagon Head Bolt

(for Use with Cover Plate DP)

Type AS





Hexagon Head Bolt AS (according to DIN 931 / 933 or ANSI / ASME B18.2.1.)
Dimensions applicable only when used with Cover Plate DP

Ordering Codes

Hexagon Head Bolt
***AS-*M6x30-DIN931/933-8.8-*W3**

* Type of bolt	Hexagon Head Bolt (according to DIN 931 / 933 or ANSI / ASME B18.2.1.)	**AS**
* Thread type and size acc. to dimension table		**M6x30-DIN931/933-8.8**
* Material code	Carbon Steel, zinc/nickel-plated	**W3**
	Stainless Steel V2A 1.4301 / 1.4305 (AISI 304 / 303)	**W4**
	Stainless Steel V4A 1.4401 / 1.4571 (AISI 316 / 316 Ti)	**W5**

All threaded parts are available with Metric ISO thread or unified coarse (UNC) thread according to dimension table. Alternative materials and surface finishings are available upon request.

Group STAUFF	DIN	Dimensions (mm/in) Thread G x L	Ordering Codes (Standard Options)
1	0	M6 x 30	AS-M6x30-DIN931/933-8.8-W3
		1/4–20 UNC x 1-1/4	AS-1/4-20UNCx1-1/4-AB-GR5-W3
1A	1	M6 x 30	AS-M6x30-DIN931/933-8.8-W3
		1/4–20 UNC x 1-1/4	AS-1/4-20UNCx1-1/4-AB-GR5-W3
2	2	M6 x 35	AS-M6x35-DIN931/933-8.8-W3
		1/4–20 UNC x 1-3/8	AS-1/4-20UNCx1-3/8-AB-GR5-W3
3	3	M6 x 40	AS-M6x40-DIN931/933-8.8-W3
		1/4–20 UNC x 1-1/2	AS-1/4-20UNCx1-1/2-AB-GR5-W3
4	4	M6 x 45	AS-M6x45-DIN931/933-8.8-W3
		1/4–20 UNC x 1-7/8	AS-1/4-20UNCx1-7/8-AB-GR5-W3
5	5	M6 x 60	AS-M6x60-DIN931/933-8.8-W3
		1/4–20 UNC x 2-3/8	AS-1/4-20UNCx2-3/8-AB-GR5-W3
6	6	M6 x 70	AS-M6x70-DIN931/933-8.8-W3
		1/4–20 UNC x 2-3/4	AS-1/4-20UNCx2-3/4-AB-GR5-W3
7	7	M6 x 100	AS-M6x100-DIN931/933-8.8-W3
		1/4–20 UNC x 4	AS-1/4-20UNCx4-AB-GR5-W3
8	8	M6 x 125	AS-M6x125-DIN931/933-8.8-W3
		1/4–20 UNC x 4-7/8	AS-1/4-20UNCx4-7/8-AB-GR5-W3
7M		M10 x 110	AS-M10x110-DIN931/933-8.8-W3
		3/8-16 UNC x 4-1/3	AS-3/8-16 UNC x 4-1/3-AB-GR5-W3
8M		M10 x 145	AS-M10x145-DIN931/933-8.8-W3
		3/8-16 UNC x 5-6/8	AS-3/8-16 UNC x 5-6/8-AB-GR5-W3