

## ■ QUICK-ADAPTERS

- for high pressure hoses and nozzle tubes with hydraulic coupler

### Quick-adapter, short



· allows for the flexible combination with various UMETA accessory parts

length  
weight  
outer Ø

32 mm  
45 g  
20 mm

#### Connection

M 8 x 1  
M 10 x 1  
R 1/8

Ref. No.:  
9907126  
9907127  
9907128

### 200/M 1



· for button-head nipples M 1 (Ø 16) acc. to DIN 3404  
· button-head coupler made of aluminium

length  
height  
weight  
outer Ø

105 mm  
28 mm  
110 g  
24 mm

#### Type

200/M 1

Ref. No.:  
7321651

### 200/M 4



· for button-head nipples M 4 (Ø 10) acc. to DIN 3404  
· button-head coupler made of steel

length  
height  
weight  
outer Ø

107 mm  
28.5 mm  
100 g  
18 mm

#### Type

200/M 4

Ref. No.:  
7321851

### 200/M 22



· for button-head nipples M 22 (Ø 22) acc. to DIN 3404  
· button-head coupler made of aluminium

length  
height  
weight  
outer Ø

114 mm  
38.5 mm  
160 g  
32 mm

#### Type

200/M 22

Ref. No.:  
7321751

### 200/K



· for cardan shafts, with hollow nozzle

length  
weight

133 mm  
80 g

#### Type

200/K

Ref. No.:  
7322451

### 200/S



· for flush-type nipples acc. to DIN 3405

length  
weight

92 mm  
65 g

#### Type

200/S

Ref. No.:  
7321151

### 200/XS



· hard to reach areas, for cardan shafts and smallest nipples of any kind

length  
weight  
pin point tube  
outer Ø  
inner Ø  
length

95 mm  
60 g  
4 mm  
0.8 mm  
55 mm

#### Type

200/XS

Ref. No.:  
7321551

### Quick-adapters in a handy carrying case



consisting of:

each 1 x  
200/M 1  
200/M 4  
200/M 22  
200/K  
200/S  
200/XS  
swivel joint

Ref. No.:  
9230004