

DKM 90° DKM 90°

Leichte Baureihe

Metrisches Feingewinde, zylindrisch

Abdichtung: Dichtkegelanschluss 60° mit gecrimpter Mutter

Light duty

Metric fine thread, cylindric

Sealing: cone connection 60° with crimped nut

PN (bar)	Dash	DN	Inch	Gewinde (G) Thread (G)	H (mm)	K (mm)	L (mm)	SW (mm) AF (mm)	Art.-Nr. Item-No.
280	-03	5	3/16"	M 10X1	21	23	46	14	424 20 05 10
280	-03	5	3/16"	M 12X1,5	21	24	46	15	424 20 05 12
280	-04	6	1/4"	M 10X1	26	28	54	17	424 20 06 10
280	-04	6	1/4"	M 12X1,5	26	26	54	15	424 20 06 12
280	-04	6	1/4"	M 14X1,5	26	28	54	17	424 20 06 14
280	-04	6	1/4"	M 16X1,5	26	29	54	19	424 20 06 16
280	-04	6	1/4"	M 18X1,5	26	32	54	22	424 20 06 18
280	-05	8	5/16"	M 14X1,5	28	31	56	17	424 20 08 14
280	-05	8	5/16"	M 16X1,5	28	30	56	19	424 20 08 16
280	-05	8	5/16"	M 18X1,5	28	34	56	22	424 20 08 18
280	-06	10	3/8"	M 14X1,5	31	34	61	17	424 20 10 14
280	-06	10	3/8"	M 16X1,5	31	31	61	19	424 20 10 16
280	-06	10	3/8"	M 18X1,5	31	35	61	22	424 20 10 18
280	-06	10	3/8"	M 20X1,5	31	36	61	24	424 20 10 20
280	-06	10	3/8"	M 22X1,5	31	38	61	27	424 20 10 22
280	-08	12	1/2"	M 18X1,5	37	42	70	22	424 20 12 18
280	-08	12	1/2"	M 20X1,5	37	40	70	24	424 20 12 20
280	-08	12	1/2"	M 22X1,5	37	42	70	27	424 20 12 22
280	-08	12	1/2"	M 24X1,5	37	43	70	30	424 20 12 24
210	-08	12	1/2"	M 26X1,5	37	48	70	32	424 20 12 26
210	-10	16	5/8"	M 22X1,5	45	50	80	27	424 20 16 22
210	-10	16	5/8"	M 24X1,5	45	46	80	30	424 20 16 24
210	-10	16	5/8"	M 26X1,5	45	50	80	32	424 20 16 26
210	-10	16	5/8"	M 27X1,5	45	50	80	32	424 20 16 27
210	-12	19	3/4"	M 26X1,5	54	56	95	32	424 20 20 26
210	-12	19	3/4"	M 27X1,5	54	56	95	32	424 20 20 27
210	-12	19	3/4"	M 30X1,5	54	70	95	36	424 20 20 30
165	-16	25	1"	M 38X1,5	70	71	121	46	424 20 25 38
125	-20	31	1 1/4"	M 45X1,5	84	83	142	50	424 20 32 45
100	-24	38	1 1/2"	M 52X1,5	100	96	165	60	424 20 40 52

