

Gerade Adapter Straight adapters



Werkstoff: Messing
Abdichtung: durch O-Ring
Material: brass
Sealing: by O-ring

Innengewinde Inner screw-thread	Einschraubgewinde Screw-in thread	SW (mm) AF (mm)	Art.-Nr. Item-No.
1/4"-18 NPTF	M 16X1,5	22	321 210
3/8"-18 NPTF	M 16X1,5	22	321 211
1/8"-27 NPTF	M 12X1,5	27	321 199
1/4"-18 NPTF	M 14X1,5	22	321 200
M 12X1,5	M 16X1,5	22	321 213
M 12X1,5	M 22X1,5	28	321 215
M 16X1,5	M 22X1,5	28	321 216
M 16X1,5	M 26X1,5	32	321 218
M 12X1,5	1/4"-18 NPT	18	321 206
M 16X1,5	1/4"-18 NPT	22	321 207

Gerade Einschraubverschraubungen Straight screw-in unions



Werkstoff: Messing
Abdichtung: durch O-Ring
Material: brass
Sealing: by O-ring

RA PJ	Anschlussgewinde Connecting thread	Einschraubgewinde Screw-in thread	SW (mm) AF (mm)	Art.-Nr. Item-No.
L06	M 12X1,5	M 10X1	16	321 191
L06	M 12X1,5	M 16X1,5	22	321 192
L10	M 16X1,5	M 12X1,5	18	321 193
L10	M 16X1,5	M 16X1,5	22	321 194
L12	M 18X1,5	M 16X1,5	22	321 195

Gerade Schottverschraubungen Straight bulkhead unions



Werkstoff: Messing
Abdichtung: durch O-Ring
Material: brass
Sealing: by O-ring

Einschraubgewinde Screw-in thread	Schottgewinde Bulkhead thread	Länge Schottgewinde (mm) Length bulkhead thread (mm)	SW (mm) AF (mm)	Art.-Nr. Item-No.
M 12X1,5	M 12X1,5	24	18	321 961
M 14X1,5	M 12X1,5	24	20	321 962
M 16X1,5	M 16X1,5	24	22	321 163
M 16X1,5	M 16X1,5	35	22	321 965
M 16X1,5	M 22X1,5	24	28	321 968