

Anschluss-Stutzen Connection nozzles



Werkstoff: Messing
Material: brass

Baugröße Series	Stutzen-Ø (mm) Socket-Ø (mm)	Einschraubgewinde Screw-in thread	SW (mm) AF (mm)	Art.-Nr. Item-No.
1	15	M 10X1	18	322 126
1	15	M 12X1,5	18	322 127
1	15	M 14X1,5	20	322 128
1	15	M 16X1,5	22	322 129
1	15	R 1/8" - 28 keg.	16	322 133
1	15	1/8" - 27 NPT	16	322 130
1	15	1/4" - 18 NPT	16	322 131
1	15	3/8" - 18 NPT	18	322 132
2	17	M 10X1	17	322 136
2	17	M 12X1,5	18	322 137
2	17	M 14X1,5	20	322 138
2	17	M 16X1,5	22	322 139
2	17	M 22X1,5	28	322 140
2	17	G 1/4" - 19	20	322 143
2	17	G 3/8" - 19	22	322 144
2	17	1/8" - 27 NPT	18	322 134
2	17	1/4" - 18 NPT	18	322 135
2	17	3/8" - 18 NPT	18	322 141
2	17	1/2" - 14 NPT	22	322 142
3	20	M 16X1,5	22	322 149
3	20	M 22X1,5	28	322 150
3	20	M 26X1,5	32	322 125
3	20	R 3/8" - 19 keg.	22	322 124
3	20	3/8" - 18 NPT	22	322 146
3	20	1/2" - 14 NPT	22	322 147



Ausführung: lang
Werkstoff: Messing
Abdichtung: durch O-Ring
Version: long
Material: brass
Sealing: by O-ring

Baugröße Series	Stutzen-Ø (mm) Socket-Ø (mm)	Einschraubgewinde Screw-in thread	Länge (mm) Length (mm)	SW (mm) AF (mm)	Art.-Nr. Item-No.
1	15	M 16X1,5	42	22	322 151
2	17	M 12X1,5	37	18	322 148
2	17	M 14X1,5	48	20	322 152
2	17	M 14X1,5	60	20	322 153
2	17	M 22X1,5	42	28	322 201