



Clamp Body ■ Profiled Design

Profiled Inside Surface with Tension Clearance



Ordering Codes

Clamp Body

***3*006-*PP**

One clamp body is consisting of two clamp halves.

- * 1st part of STAUFF Group
- * Exact outside diameter Ø D1 (mm)
- * Material code (see below)

**3
006
PP**

Standard Materials



Polypropylene

Colour: Green

Material code: **PP**



Polypropylene

Colour: Black

Material code: **PP-BK**



Polyamide

Colour: Black

Material code: **PA**



Thermoplastic Elastomer (87 Shore-A)

Colour: Black

Material code: **SA87**



Aluminium

Colour: Self-Colour

Material code: **AL**

See pages 178 / 179 for material properties and technical information.

Special Materials

Please contact STAUFF for further details on fire-proof clamp body materials, tested and approved according to several international fire-protection standards (such as BS 6853, EN 45545-2, UL 94 and many more).

See pages 180 / 181 for material properties and technical information.

Product Features

- Proven, tested and trusted product in various markets
- Recommended for the safe installation of rigid pipes and tubes
- Available for all commonly used pipe and tube outside diameters
- Environmental protection due to vibration/noise reducing design
- Excellent weathering resistance, even under extreme conditions



Group	STAUFF	DIN	Outside Diameter		Nominal Bore		Ordering Codes (2 Clamp Halves) (** = Material)	Dimensions (mm/in)					
			Pipe / Tube Ø D1 (mm)	(in)	Pipe (in)	Copper Tube ASTM B88 (in)		L1 PP/PA/SA	L1 AL	L2	H	S min.	Width
3S	1		6				3006-**-						
			6,4	1/4			3006.4-**-						
			8	5/16			3008-**-						
			9,5	3/8		1/4	3009.5-**-						
			10		1/8		3010-**-						
			12				3012-**-						
			12,7	1/2		3/8	3012.7-**-	55	56	33	32	0,6	30,5
			13,5		1/4		3013.5-**-	2.16	2.20	1.30	1.26	.02	1.20
			14				3014-**-						
			15				3015-**-						
			16	5/8		1/2	3016-**-						
			17,2		3/8		3017.2-**-						
			18				3018-**-						
			20				3020-**-						
4S	2		19	3/4			4019-**-						
			20				4020-**-						
			21,3		1/2		4021.3-**-						
			22	7/8		3/4	4022-**-	70	70	45	48	0,6	30,5
			25				4025-**-	2.76	2.76	1.77	1.89	.02	1.20
			25,4	1			4025.4-**-						
			26,9		3/4		4026.9-**-						
			28				4028-**-						
			30				4030-**-						
			30				5030-**-						
5S	3		32	1-1/4			5032-**-						
			33,7		1		5033.7-**-						
			35			1-1/4	5035-**-	85	85	60	60	0,6	30,5
			38	1-1/2			5038-**-	3.35	3.35	2.36	2.36	.02	1.20
			40				5040-**-						
			41,3			1-1/2	5041.3-**-						
			42		1-1/4		5042-**-						
			38	1-1/2			6038-**-						
			42		1-1/4		6042-**-						
			44,5	1-3/4			6044.5-**-						
6S	4		48,3		1-1/2		6048.3-**-						
			50,8	2			6050.8-**-						
			54			2	6054-**-	115	120	90	89	2	45
			55				6055-**-	4.53	4.72	3.54	3.50	.08	1.77
			57				6057-**-						
			57,2	2-1/4			6057.2-**-						
			60,3		2		6060.3-**-						
			63,5	2-1/2			6063.5-**-						
			65				6065-**-						
			70	2-3/4			6070-**-						

See page 39 for STAUFF Group 7S to 12S (DIN Group 5 to 10).

Additional outside diameters are available upon request. Please contact STAUFF for further information.

Clamp Body - Profiled Design

Profiled Inside Surface with Tension Clearance



B

Group	DIN	Outside Diameter		Nominal Bore	Ordering Codes (2 Clamp Halves) (** = Material)	Dimensions (mm/in)					
		Pipe / Tube Ø D1 (mm)	(in)			L1 PP/PA	L1 AL	L2	H	S min.	Width
7S	5	60,3			7060.3-**-**						
		65			7065-**-**						
		70	2-3/4		7070-**-**						
		73		2-1/2 (ANSI B 36-10)	7073-**-**						
		75			7075-**-**						
		76,1	3	2-1/2 (DIN EN 10220)	7076.1-**-**						
		80			7080-**-**						
		82,5			7082.5-**-**						
8S	6	88,9	3-1/2	3	7088.9-**-**	154	152	122	120	2	60
						6.06	5.98	4.80	4.72	.08	2.36
		88,9	3-1/2	3	8088.9-**-**						
		100			8100-**-**						
		102	4	3-1/2	8102-**-**	206	208	168	168	2	80
		108			8108-**-**	8.11	8.19	6.61	6.61	.08	3.15
		114	4-1/2	4	8114-**-**						
		127	5		8127-**-**						
9S	7	133			8133-**-**						
		127	5		9127-**-**						
		133			9133-**-**						
		140		5	9140-**-**	251	255	205	200	3	91
		152	6		9152-**-**	9.88	10.04	8.07	7.87	.12	3.58
		159			9159-**-**						
		165			9165-**-**						
		168		6	9168-**-**						
10S	8	168		6	10168-**-**						
		177,8			10177.8-**-**						
		193,7			10193.7-**-**	336	326	265	270	3	120
		203	8		10203-**-**	13.22	12.83	10.43	10.63	.12	4.72
		216			10216-**-**						
		219		8	10219-**-**						
		219		8	11219-**-**	470	470	395	410	8	162
		273		10	11273-**-**	18.50	18.50	15.55	16.14	.31	6.38
11S	9	324		12	11324-**-**						
		356		14	12356-**-**	630	630	534	530	20	182
12S	10	406		16	12406-**-**	24.80	24.80	21.02	20.87	.79	7.16

See page 38 for STAUFF Group 3S to 6S (DIN Group 1 to 4).

Additional outside diameters are available upon request. Please contact STAUFF for further information.

Ordering Codes

Clamp Body

***7*060.3-*PP**

One clamp body is consisting of two clamp halves.

- * 1st part of STAUFF Group
- * Exact outside diameter Ø D1 (mm)
- * Material code (see below)

**7
060.3
PP**

Standard Materials



Polypropylene
Colour: Green
Material code: **PP**



Polypropylene
Colour: Black
Material code: **PP-BK**



Polyamide
Colour: Black
Material code: **PA**



Aluminium
Colour: Self-Colour
Material code: **AL**

See pages 178 / 179 for material properties and technical information.

Special Materials

Please contact STAUFF for further details on fire-proof clamp body materials, tested and approved according to several international fire-protection standards (such as BS 6853, EN 45545-2, UL 94 and many more).

See pages 180 / 181 for material properties and technical information.

Product Features

- Proven, tested and trusted product in various markets
- Recommended for the safe installation of rigid pipes and tubes
- Available for all commonly used pipe and tube outside diameters
- Environmental protection due to vibration/noise reducing design
- Excellent weathering resistance, even under extreme conditions