




Clamp Body - Profiled Design

Profiled Inside Surface with Tension Clearance



STAUFF Group 1



STAUFF Group 1A to 8

Ordering Codes

Clamp Body

Clamp Body, STAUFF Group 1A

*1*06-*PP

*1*06A-*PP

One clamp body is consisting of two clamp halves.

- * STAUFF Group
- * Exact outside diameter Ø D1 (mm)
- * Material code (see below)

1
06
PP

Standard Materials



Polypropylene

Colour: Green

Material code: **PP**



Polypropylene

Colour: Black

Material code: **PP-BK**



Polyamide

Colour: Black

Material code: **PA**



Thermoplastic Elastomer (87 Shore-A)

Colour: Black

Material code: **SA87**



Aluminium

Colour: Self-Colour

Material code: **AL** (STAUFF Group 1A to 6)

See pages 178 / 179 for material properties and technical information.

Special Materials

Please contact STAUFF for further details on fire-proof clamp body materials, tested and approved according to several international fire-protection standards (such as BS 6853, EN 45545-2, UL 94 and many more).

See pages 180 / 181 for material properties and technical information.

Product Features

- Proven, tested and trusted product in various markets
- Recommended for the safe installation of rigid pipes and tubes
- Available for all commonly used pipe and tube outside diameters
- Environmental protection due to vibration/noise reducing design
- Excellent weathering resistance, even under extreme conditions

Group	STAUFF	DIN	Outside Diameter		Nominal Bore		Ordering Codes (2 Clamp Halves)	Dimensions (^{mm} / _{in})						
			Pipe / Tube Ø D1 (mm)	(in)	Pipe (in)	Copper Tube ASTM B88 (in)		L1	L2	H	S min.	Width		
1	0		6				106-***	28	1.10	.37	27	0,4	.02	1.18
		6,4	1/4			106.4-***								
		8	5/16			108-***								
		9,5	3/8		1/4	109.5-***								
		10		1/8		110-***								
		12				112-***								
1A	1		6				106A-***	37	1.46	20	27	0,4	.02	1.18
		6,4	1/4			106.4A-***								
		8	5/16			108A-***								
		9,5	3/8		1/4	109.5A-***								
		10		1/8		110A-***								
		12				112A-***								
2	2	12,7	1/2		3/8	212.7-***	42	1.65	26	1.02	33	0,6	.02	1.18
		13,5		1/4		213.5-***								
		14				214-***								
		15				215-***								
		16	5/8		1/2	216-***								
		17,2		3/8		217.2-***								
		18				218-***								
		19	3/4			319-***								
3	3	20				320-***	50	1.97	33	1.30	36	0,6	.02	1.18
		21,3		1/2		321.3-***								
		22	7/8		3/4	322-***								
		25				325-***								
		25,4	1			325.4-***								
		26,9		3/4		426.9-***								
4	4	28				428-***	59	2.32	40	1.57	42	0,6	.02	1.18
		28,6			1	428.6-***								
		30				430-***								
		32				432-***								
		32	1-1/4			532-***								
5	5	33,7		1		533.7-***	71	2.80	52	2.05	58	0,8	.03	1.18
		35			1-1/4	535-***								
		38	1-1/2			538-***								
		40				540-***								
		41,3		1-1/2		541.3-***								
		42		1-1/4		542-***								
6	6	44,5	1-3/4			644.5-***	86	3.39	66	2.60	66	0,8	.03	1.18
		48,3		1-1/2		648.3-***								
		50,8	2			650.8-***								
		54		2		654-***								
7	7	57,2	2-1/4			757.2-***	121	4.76	94	3.70	93	0,8	.03	1.18
		60,3		2		760.3-***								
		63,5	2-1/2			763.5-***								
		70	2-3/4			770-***								
		73		2-1/2 (ANSI B 36-10)		773-***								
		76,1	3	2-1/2 (DIN EN 10220)		776.1-***								
8	8	88,9		3		888.9-***	147	5.79	120	4.72	118	0,8	.03	1.18
		102	4	3-1/2		8102L-***								

Additional outside diameters are available upon request. Please contact STAUFF for further information.

Dimensional drawings: All dimensions in mm (in).