



Angled Weld Plate Type WSP



STAUFF Group 1

STAUFF Group 1A to 6 (7M / 8M)

Ordering Codes

Weld Plate

***WSP-*1-*M-*W2**

* Angled Weld Plate

WSP

* STAUFF Group

1

* Thread code

Metric ISO thread

M

Unified coarse (UNC) thread

U

* Material code

Carbon Steel, phosphated

W2

Carbon Steel, zinc/nickel-plated

W3

Stainless Steel V2A

W4

1.4301 / 1.4305 (AISI 304 / 303)

Stainless Steel V4A



W5

1.4401 / 1.4571 (AISI 316 / 316 Ti)

Group STAUFF	DIN	Dimensions (mm/in) Thread G	L1	L2	B1	B2	S	H	ØD1	ØD2	Ordering Codes (Standard Options)
1	0	M6	30	14	30	30	3	6,5	12	6,5	WSP-1-M-W2
		1/4-20 UNC	1.18	.55	1.18	1.18	.12	.26	.47	.26	WSP-1-U-W2
1A	1	M6	36	20	30	30	3	6,5	12	6,5	WSP-1A-M-W2
		1/4-20 UNC	1.26	.79	1.18	1.18	.12	.26	.47	.26	WSP-1A-U-W2
2	2	M6	42	26	30	30	3	6,5	12	6,5	WSP-2-M-W2
		1/4-20 UNC	1.65	1.02	1.18	1.18	.12	.26	.47	.26	WSP-2-U-W2
3	3	M6	50	33	30	30	3	6,5	12	6,5	WSP-3-M-W2
		1/4-20 UNC	1.97	1.30	1.18	1.18	.12	.26	.47	.26	WSP-3-U-W2
4	4	M6	60	40	30	30	3	6,5	12	6,5	WSP-4-M-W2
		1/4-20 UNC	2.36	1.57	1.18	1.18	.12	.26	.47	.26	WSP-4-U-W2
5	5	M6	70	52	30	30	3	6,5	12	6,5	WSP-5-M-W2
		1/4-20 UNC	2.76	2.05	1.18	1.18	.12	.26	.47	.26	WSP-5-U-W2
6	6	M6	88	66	30	30	3	6,5	12	6,5	WSP-6-M-W2
		1/4-20 UNC	3.46	2.60	1.18	1.18	.12	.26	.47	.26	WSP-6-U-W2
7M		M10	125	100	50	50	8	5,3	18	6,5	WSP-7M-M-W2
		3/8-16 UNC	4.92	3.94	1.97	1.97	.31	.21	.71	.26	WSP-7M-U-W2
8M		M10	165	140	50	50	8	5,3	18	6,5	WSP-8M-M-W2
		3/8-16 UNC	6.50	5.51	1.97	1.97	.31	.21	.71	.26	WSP-8M-U-W2

All threaded parts are available with Metric ISO thread or unified coarse (UNC) thread according to dimension table. Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.

Bridge Weld Plate Type BSP



Ordering Codes

Weld Plate

***BSP-*1A-*M-*W2**

* Bridge Weld Plate

BSP

* STAUFF Group

1A

* Thread code

Metric ISO thread

M

Unified coarse (UNC) thread

U

* Material code

Carbon Steel, phosphated

W2

Carbon Steel, zinc/nickel-plated

W3

Stainless Steel V2A

W4

1.4301 / 1.4305 (AISI 304 / 303)

Stainless Steel V4A

W5

1.4401 / 1.4571 (AISI 316 / 316 Ti)

Group STAUFF	DIN	Dimensions (mm/in) Thread G	L1	L2	B	S	H1	H2	ØD	Ordering Codes (Standard Options)
1A	1	M6	48	20	30	3	13	6,5	12	BSP-1A-M-W2
		1/4-20 UNC	1.89	.79	1.18	.12	.52	.26	.47	BSP-1A-U-W2
2	2	M6	54	26	30	3	13	6,5	12	BSP-2-M-W2
		1/4-20 UNC	2.13	1.02	1.18	.12	.52	.26	.47	BSP-2-U-W2
3	3	M6	62	33	30	3	13	6,5	12	BSP-3-M-W2
		1/4-20 UNC	2.44	1.30	1.18	.12	.52	.26	.47	BSP-3-U-W2
4	4	M6	71	40	30	3	13	6,5	12	BSP-4-M-W2
		1/4-20 UNC	2.80	1.57	1.18	.12	.52	.26	.47	BSP-4-U-W2
5	5	M6	85	52	30	3	13	6,5	12	BSP-5-M-W2
		1/4-20 UNC	3.35	2.05	1.18	.12	.52	.26	.47	BSP-5-U-W2
6	6	M6	98	66	30	3	13	6,5	12	BSP-6-M-W2
		1/4-20 UNC	3.86	2.60	1.18	.12	.52	.26	.47	BSP-6-U-W2

All threaded parts are available with Metric ISO thread or unified coarse (UNC) thread according to dimension table. Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.