

For the SWIVELLING version add the suffix "/SO" at the P/N, except for the 560 series.
For example: 270/10/SO

FIXED PAINTED STEEL

FIXED S. STEEL AISI 304

Supplied with:

- hose in black synthetic rubber with galvanized steel coupling
- brass swivel joint
- Viton® seals
- central shaft in galvanized steel or stainless steel AISI 304
- inlet hose 0,6 m to connect the hose reel to the system (standard on the versions with hose)



	P/N	P/N	Hose supplied	Connection	
				Inlet	Outlet
S. 270	270/10	272/10	without hose	F 3/8"G	F 3/8"G
	270/11	272/11	10m 3/8" (952/10)	F 3/8"G	M 3/8"G
	270/14	272/14	15m 1/4" (932/15)	F 3/8"G	M 1/4"G
S. 300	300/10	302/10	without hose	F 3/8"G	F 3/8"G
	300/11	302/11	12m 3/8" (952/12)	F 3/8"G	M 3/8"G
S. 350	350/10	352/10	without hose	F 3/8"G	F 3/8"G
	350/11	352/11	18m 3/8" (952/18)	F 3/8"G	M 3/8"G
	350/14	352/14	12m 3/8" (952/12)	F 3/8"G	M 3/8"G
S. 430	430/10	432/10	without hose	F 1/2"G	F 1/2"G
	430/11	432/11	15m 1/2" (962/15)	F 1/2"G	M 1/2"G
	430/12	432/12	12m 3/8" (952/13)	F 1/2"G	M 3/8"G
	430/13	432/13	18m 3/8" (952/19)	F 1/2"G	M 3/8"G
	430/14	432/14	10m 1/2" (962/10)	F 1/2"G	M 1/2"G
S. 4430 ABS	4430/10	4432/10	without hose	F 1/2"G	F 1/2"G
	4430/11	4432/11	15m 1/2" (962/15)	F 1/2"G	M 1/2"G
	4430/12	4432/12	12m 3/8" (952/13)	F 1/2"G	M 3/8"G
	4430/13	4432/13	18m 3/8" (952/19)	F 1/2"G	M 3/8"G
	4430/14	4432/14	10m 1/2" (962/10)	F 1/2"G	M 1/2"G
S. 530	530/10	532/10	without hose	F 1/2"G	F 1/2"G
	530/11	532/11	20m 1/2" (962/20)	F 1/2"G	M 1/2"G
	530/12	532/12	25m 1/2" (962/25)	F 1/2"G	M 1/2"G
S. 540	540/10	542/10	without hose	F 1"G	F 1"G
	540/11	542/11	15m 3/4" (972/15)	F 1"G	M 3/4"G
	540/12	542/12	20m 3/4" (972/20)	F 1"G	M 3/4"G
	540/13	542/13	15m 1" (982/15)	F 1"G	M 1"G
	540/15	542/15	without hose	F 1/2"G	F 1/2"G
	540/16	542/16	30m 1/2" (962/30)	F 1/2"G	M 1/2"G
S. 560	560/10	562/10	without hose	F 1"G	F 1"G
	560/11	562/11	30m 3/4" (972/30)	F 1"G	M 3/4"G
	560/12	562/12	35m 3/4" (972/35)	F 1"G	M 3/4"G
	560/13	562/13	40m 3/4" (972/40)	F 1"G	M 3/4"G
	560/14	562/14	20m 1" (982/20)	F 1"G	M 1"G
	560/15	562/15	30m 1" (982/30)	F 1"G	M 1"G
	560/16	562/16	without hose	F 1/2"G	F 1/2"G
	560/17	562/17	40m 1/2" (962/40)	F 1/2"G	M 1/2"G
	560/18	562/18	50m 1/2" (962/50)	F 1/2"G	M 1/2"G
	560/19	562/19	60m 1/2" (962/60)	F 1/2"G	M 1/2"G

Rubber handles, mounted on hose terminal part, are available for all the above series. For more information look at page 50.



Atex 94/9 **II 3GD c X**
IIB 2GD c T4 T135°C X (only for series without hose 430-530-540-560)