

15 and 16 series Thread connectors

- ISO G, ISO R and NPT threads
- Port size: M5, 1/8" ... 1"
- Extensive range of shapes and sizes including manifolds
- High temperature and pressure aluminium sealing washers supplied with ISO G threads



Technical features

Medium:

Compressed air and fluid compatible with sealing materials

Thread forms:

Parallel BSP - ISO 228
Taper BSP - ISO 7
Metric - ISO 262
Taper NPTF - ASME B1.20.1

Operating pressure:

Generally limited by tubing specification except where polyamide sealing washers are used (banjo bolts and M5 units). In these cases pressure is limited to 18 bar (261 psi). Flow regulating banjos are limited to 1 ... 10 bar (1 ... 145 psi) operating range. Suitable for vacuum applications.






















Ambient/Media temperature:

Generally limited by tubing specification except where polyamide sealing washers are used (banjo bolts, & M5 units). In these cases temperature is limited to -20 ... +70°C (-4 ... 158°F)

Materials:

Body of the fittings are made from Brass type; OT UNI EN 12164/5 CW 614/7N and undergo to a nickel-plating process. Other materials will be specified with the fitting details. All ISO G male threads supplied with flat aluminium washer unless stated otherwise.

Straight adaptors, connectors and plugs

<p>ISO G - Reducing connector 16023</p>  <p>Page 4</p>	<p>ISO G - Expanding connector 16023</p>  <p>Page 4</p>	<p>ISO G - ISO R Expanding connector 15023</p>  <p>Page 4</p>	<p>ISO G - ISO R Reducing connector 15023</p>  <p>Page 4</p>	<p>NPT - ISO R Adaptor 15423</p>  <p>Page 4</p>	<p>ISO G - NPT Adaptor 17223</p>  <p>Page 4</p>	<p>ISO G and Metric - Bulkhead connector 16029</p>  <p>Page 5</p>
<p>ISO G - Sleeve adaptor 16022</p>  <p>Page 5</p>	<p>ISO G and Metric - Nip- ple adaptor 16020</p>  <p>Page 5</p>	<p>ISO R - Nipple adaptor 15020</p>  <p>Page 5</p>	<p>ISO R - NPT - Nipple adaptor 15420</p>  <p>Page 5</p>			
<p>ISO R - Flat union 15033</p>  <p>Page 6</p>	<p>ISO R - Conical union 1503D</p>  <p>Page 6</p>	<p>ISO R - Hose adaptor 29117</p>  <p>Page 6</p>	<p>ISO G - Hose adaptor 29217</p>  <p>Page 6</p>			
<p>ISO G - Plug with flange - hex 16206</p>  <p>Page 7</p>	<p>ISO G - Plug with flange - spanner 16005</p>  <p>Page 7</p>	<p>ISO G - Plug 16213</p>  <p>Page 7</p>	<p>ISO R - Plug 1500</p>  <p>Page 7</p>	<p>ISO R - Plug 15113</p>  <p>Page 7</p>	<p>ISO R - Plug Brass (unplated) 25013</p>  <p>Page 7</p>	

Elbow adaptors and T-connectors

<p>ISO G - Elbow connector 16042</p>  <p>Page 8</p>	<p>ISO R - ISO G - Elbow connector 15043</p>  <p>Page 8</p>	<p>ISO R - Elbow connector 15040</p>  <p>Page 8</p>	<p>ISO G - Tee connector 16062</p>  <p>Page 9</p>	<p>ISO R - Tee connector 15060</p>  <p>Page 9</p>	<p>ISO R - ISO G Tee connector 15069</p>  <p>Page 9</p>	<p>ISO R - ISO G Tee connector 15072</p>  <p>Page 9</p>
<p>ISO G - Cross 16092</p>  <p>Page 9</p>	<p>ISO G - Cross block 16094</p>  <p>Page 9</p>	<p>ISO G - Manifold - singlesided - Brass 34050</p>  <p>Page 10</p>	<p>ISO G - Manifold - single sided - Aluminium 162B4 and 162B6</p>  <p>Page 10</p>	<p>ISO G - Manifold - double sided - Aluminium 162C4 and 162C6</p>  <p>Page 10</p>		

Banjo flow controls and elbows

<p>ISO G - Banjo elbow assembly - regulating out 16K51</p>  <p>Page 11</p>	<p>ISO G - Banjo elbow assembly - non-regulating 16A51</p>  <p>Page 11</p>	<p>ISO G - Banjo elbow body 16051</p>  <p>Page 11</p>	<p>ISO G - Regulating bolt 20K00, 20L00 and 20M00</p>  <p>Page 12</p>	<p>ISO G - Non-regulating bolt 20A00 and 20B00</p>  <p>Page 11</p>
---	---	--	--	---

Elbow flow controls

<p>ISO R - Elbow flow control, regulating out 10TA0</p>  <p>Page 12</p>	<p>ISO G - Elbow flow control, regulating out 10KA0</p>  <p>Page 12</p>
--	--

Function fittings

<p>ISO R - Pilot operated check valve 101GA</p>  <p>Page 13</p>	<p>ISO G - Pilot operated check valve 102GA</p>  <p>Page 13</p>	<p>ISO G - Pressure reduction valve 102GB</p>  <p>Page 13</p>	<p>ISO G - Pressure sensor valve 102GD</p>  <p>Page 13</p>
---	---	---	--

Accessories - Stainless steel

<p>Plug ISO G 66005</p>  <p>Page 14</p>	<p>Sleeve adaptor ISO G 66022</p>  <p>Page 14</p>	<p>Tee connector ISO G 66062</p>  <p>Page 14</p>
--	--	---

Seals


<p>Copper sealing washer 480213</p>  <p>Page 15</p>	<p>Bonded sealing washer 480215</p>  <p>Page 15</p>	<p>Aluminium sealing washer</p>  <p>Page 15</p>
--	--	--

Accessories

<p>PTFE sealing tape DB-R-12</p>  <p>Page 15</p>

ISO G - Reducing connector 16023

Nickel plated brass, aluminium seals




B	B1	C	G		Model
G1/8	M5	10,5	6	14	160231805
G1/4	G1/8	13	8	17	160232818
G3/8	G1/8	14	9	19	160233818
G3/8	G1/4	14	9	19	160233828
G1/2	G1/8	15,5	10	24	160234818
G1/2	G1/4	15,5	10	24	160234828
G1/2	G3/8	15,5	10	24	160234838
G3/4	G1/4	17,5	12	30	160236828
G3/4	G3/8	17,5	12	30	160236838
G3/4	G1/2	17,5	12	30	160236848

ISO G - ISO R - Reducing connector 15023

Dimensions in mm
Projection/First angle


Nickel plated brass



B	B1	C	G	G1	ØS		Model
G1/8	R1/8	20	10	7,5	5,5	14	150231818
G1/8	R1/4	16	12	11	6	14	150232818
G1/4	R1/4	26	12	11	8	17	150232828
G1/8	R3/8	16,5	12	11,5	6	17	150233818
G1/4	R3/8	16,5	11,5	13	8,5	17	150233828
G3/8	R3/8	27,5	13	11,5	11	22	150233838
G1/8	R1/2	19,5	12	7,5	5,5	22	150234818
G1/4	R1/2	19,5	13	14	9,5	22	150234828
G3/8	R1/2	19,5	13	14	14	22	150234838
G1/2	R1/2	33	16	14	15	26	150234848
G1/4	R3/4	23,5	16,5	11,5	8	27	150236828
G3/8	R3/4	23,5	11,5	16,5	20	27	150236838
G1/2	R3/4	23,5	17	16,5	16	27	150236848
G1/2	R1	26,5	19	13	15	34	150238848
G3/4	R1	27,5	19	16,5	24,5	34	150238868

ISO G - Expanding connector 16023


Nickel plated brass, aluminium seals



B	B1	C	G	G1	ØS		Model
G1/8	M5	14,5	8,5	4	2,5	14	160230518
G1/4	G1/8	20,5	12	6	5,5	17	160231828
G3/8	G1/8	21,5	10,5	6	5,5	22	160231838
G3/8	G1/4	23,5	13	8	8	22	160232838
G1/2	G1/4	26,5	16	8	8	26	160232848
G1/2	G3/8	36,5	16	9	11	26	160233848
G3/4	G1/2	31	16,5	10	15	32	160234868

NPT Female - ISO R - Adaptor 15423


Nickel plated brass



B	B1	C	G	G1	ØS		Model
1/8 NPT	R1/8	17	9,5	6	5,5	14	154231818
1/4 NPT	R1/4	23	13,5	8	8	17	154232828
3/8 NPT	R3/8	24	13,5	9	11	22	154233838
1/2 NPT	R1/2	31,5	17,5	12	14,5	27	154234848

ISO G - ISO R - Expanding connector 15023


Nickel plated brass



B	B1	C	G	G1	ØS		Model
G1/4	R1/8	22	12,5	7,5	5,5	17	150231828
G3/8	R1/8	22,5	7,5	10,5	5	22	150231838
G3/8	R1/4	27	13	11	8	22	150232838
G1/2	R1/4	30	16	11	8	26	150232848
G1/2	R3/8	30,5	16	11	11	26	150233848
G3/4	R3/8	38,5	12,5	16,5	11	32	150233868
G3/4	R1/2	35	16,5	14	15	32	150234868
G1	R3/4	45	19	19	18	41	150236888

ISO G Female - NPT - Adaptor 17223


Nickel plated brass



B	B1	C	G	G1	ØS		Model
G1/4	1/4 NPT	27	12	13	8	17	172232828
G3/8	3/8 NPT	28	13	13	11	22	172233838

ISO G and Metric - Bulkhead connector 16029


Nickel plated brass



B	B1	C	F	G max.			Model
M5	M10x1,0	14	3,5	7	14	14	160290005
G1/8	M16x1,5	18	4	10	19	22	160290018
G1/4	M20x1,5	25	4	16	24	27	160290028
G3/8	M26x1,5	26	5	15	30	32	160290038
G1/2	M28x1,5	33	6	21	32	36	160290048
G3/4	M33x1,5	36,5	6	22,5	41	41	160290068
G1	M42x1,5	41,5	8	24,5	46	50	160290088

ISO G and Metric - Sleeve adaptor 16022


Nickel plated brass



B	B1	C	G		Model
M5	M5	11	11	8	160220505
G1/8	M5	13	7,5	14	160221805
G1/8	G1/8	15	15	14	160221818
G1/4	G1/8	19	11	17	160222818
G1/4	G1/4	22	22	17	160222828
G3/8	G1/8	20	11,5	22	160223818
G3/8	G1/4	23	11,5	22	160223828
G3/8	G3/8	24	24	22	160223838
G1/2	G1/8	24	14	24	160224818
G1/2	G1/4	25	14	24	160224828
G1/2	G3/8	27,5	16	24	160224838
G1/2	G1/2	30	30	26	160224848
G3/4	G1/2	30	16,5	30	160226848
G3/4	G3/4	32	31	32	160226868
G1	G3/4	41	20	40	160228868

NPT - ISO R - Nipple adaptor 15420


Nickel plated brass



B	B1	C	G	G1	Ø S		Model
1/8 NPT	R1/8	21,5	8,5	8,5	5,5	12	154201818
1/4 NPT	R1/4	31	13	13	8	14	154202828
3/8 NPT	R3/8	31	13	13	11	19	154203838
1/2 NPT	R1/2	40	17	17	16,5	22	154204848

ISO G and Metric - Nipple adaptor 16020


Nickel plated brass, aluminium seals



B	B1	C	G	G1	Ø S	Ø S1		Model
M5	M5	11,5	4	4	2,5	2,5	8	160200505
G1/8	M5	14,5	6	4	5,5	3,5	14	160201805
G1/8	G1/8	16,5	6	6	5,5	5,5	14	160201818
G1/4	G1/8	19	8	6	8	5,5	17	160202818
G1/4	G1/4	21	8	8	8	8	17	160202828
G3/8	G1/4	22	9	8	11	8	19	160203828
G3/8	G3/8	23	9	9	11	11	19	160203838
G1/2	G1/4	23,5	10	8	15	8	24	160204828
G1/2	G3/8	24,5	10	9	15	11	24	160204838
G1/2	G1/2	25,5	10	10	15	15	24	160204848
G3/4	G1/2	27,5	12	10	20	15	30	160206848
G3/4	G3/4	29,5	12	12	20	20	30	160206868
G1	G1	32	12	12	24	40	160208888	

ISO R - Nipple adaptor 15020


Nickel plated brass



B	B1	C	G	G1	Ø S	Ø S1		Model
R1/8	R1/8	19,5	7,5	7,5	5,5	5,5	12	150201818
R1/4	R1/8	23,5	11	7,5	8	5,5	14	150202818
R1/4	R1/4	27	11	11	8	8	14	150202828
R3/8	R1/8	24	11,5	7,5	11	5,5	17	150203818
R3/8	R1/4	27,5	11,5	11	11	8	17	150203828
R3/8	R3/8	28	11,5	11,5	11	11	17	150203838
R1/2	R1/8	27	14	7,5	15	5,5	22	150204818
R1/2	R1/4	30,5	14	11	15	8	22	150204828
R1/2	R3/8	31	14	11,5	15	11	22	150204838
R1/2	R1/2	33,5	14	14	15	15	22	150204848
R3/4	R1/2	37,5	16,5	14	19	15	27	150206848
R3/4	R 3/4	40	16,5	16,5	19	19	27	150206868
R1	R3/4	44	19	16,5	24	19	34	150208868
R1	R1	46,5	19	19	24	24	34	150208888

ISO R - Flat union 15033


Nickel plated brass, O-ring NBR
Temperature: -20 ... +80°C
Operating pressure: -1 ... +15 bar



B	C	F	G			Model
R1/8	33,5	10	8,5	5	15	150331818
R1/4	42	13	10,5	8	24	150332828
R3/8	43	13	11	10	27	150333838
R1/2	52	17,5	11,5	14	30	150334848
R3/4	56,5	19	12,5	17	38	150336868
R1	68	23	16	19	46	150338888

ISO R - Conical union 1503D


Brass, O-ring NBR
Temperature: -20 ... +80°C
Operating pressure: -1 ... +15 bar



B	C	F	G			Model
R1/8	27	9	8,5	5	15	1503D1818
R1/4	33,5	11,5	9,5	6	19	1503D2828
R3/8	36,5	13	10	8	22	1503D3838
R1/2	45	16	12	12	27	1503D4848
R3/4	54	18	17	14	36	1503D6868
R1	65	21,5	20	19	46	1503D8888

ISO R - Hose adaptor 29117


Nickel plated brass



Ø A	B	C	G	L		Ø Z	Model
4	R1/8	32	7,5	19,5	12	6	291170418
4	R1/4	35,5	11	19,5	14	6	291170428
6	R1/8	32	7,5	19,5	12	8	291170618
6	R1/4	35,5	11	19,5	14	8	291170628
6	R3/8	36	11,5	19,5	17	8	291170638
7	R1/8	32	7,5	19,5	14	9	291170718
7	R1/4	35	11	19,5	17	9	291170728
7	R3/8	36	11,5	19,5	17	9	291170738
8	R1/8	32	7,5	19,5	12	10	291170818
8	R1/4	35,5	11	19,5	14	10	291170828
8	R3/8	36	11,5	19,5	17	10	291170838
8	R1/2	39	14	19,5	22	10	291170848
9	R1/8	32	7,5	19,5	12	11	291170918
9	R1/4	35,5	11	19,5	14	11	291170928
9	R3/8	36	11,5	19,5	17	11	291170938
9	R1/2	39	14	19,5	17	11	291170948
10	R1/4	35,5	11	19,5	14	12	291171028
10	R3/8	36	11,5	19,5	17	12	291171038
10	R1/2	39	14	19,5	22	12	291171048
12	R3/8	36	11,5	19,5	17	14	291171238
12	R1/2	39	14	19,5	22	14	291171248
13	R1/4	35,5	11	19,5	22	15	291171328
13	R3/8	36	11,5	19,5	17	15	291171338
13	R1/2	39	14	19,5	22	15	291171348
13	R3/4	43,5	14,5	19,5	27	15	291171368
16	R3/8	36	11,5	19,5	19	18	291171638
16	R1/2	39	14	19,5	22	18	291171648
16	R3/4	43,5	16,5	19,5	27	18	291171668
19	R3/8	47,5	11,5	30	22	21	291171938
19	R1/2	49,5	14	30	22	21	291171948
19	R3/4	54	16,5	30	27	21	291171968
25	R3/4	52,5	14,5	30	28	27	291172568
25	R1	53,5	16	30	34	27	291172588
32	R1	55	16	30	36	34	291173288

Metric and ISO G - Hose adaptor 29217


Nickel plated brass, aluminium seals



Ø A	B	C	G	L		Ø Z	Model
3	M5	15,5	4	7,5	8	3,5	292170305
4	G1/8	30	6	20	14	6,5	292170418
4	G1/4	33	8	20	17	6,5	292170428
5	G1/8	30	6	20	14	7,5	292170518
6	G1/8	30	6	20	14	8,5	292170618
6	G1/4	33	8	20	17	8,5	292170628
9	G1/8	30	6	20	14	11,5	292170918
9	G1/4	33	8	20	17	11,5	292170928
9	G3/8	34	9	20	19	11,5	292170938
9	G1/2	35,5	10	20	24	11,5	292170948
10	G1/4	33	8	20	17	12,5	292171028
10	G3/8	34	9	20	19	12,5	292171038
10	G1/2	37,5	10	22	24	12,5	292171048
13	G1/4	33	8	20	17	15,5	292171328
13	G3/8	34	9	20	19	15,5	292171338
13	G1/2	37,5	10	22	24	15,5	292171348
13	G3/4	39,5	12	22	30	15,5	292171368
19	G3/4	41,5	12	24	30	21,5	292171968

Metric and ISO G - Plug with flange - spanner 16005


Nickel plated brass, aluminium seals



B	C	G		Model
M5	8	4,5	8	160050005
G1/8	10	6,5	14	160050018
G1/4	13	9	17	160050028
G3/8	13,5	9,5	19	160050038
G1/2	14,5	10	24	160050048
G3/4	16	11	30	160050068
G1	17	12	40	160050088

ISO G - Plug with flange - hex 16206

Nickel plated brass, O-ring NBR
Temperature: -20 ... +80°C
Operating pressure: -1 ... +15 bar




Dimensions in mm
Projection/First angle



B	C	G	ØD		Model
M5	6	4	8	2	162060005
G1/8	8,5	6	14	5	162060018
G1/4	11	8	17	6	162060028
G3/8	12,5	9	20	8	162060038
G1/2	13,5	10	25	10	162060048

ISO G - Plug 16213


Nickel plated brass



B	C	C1	ØD		Model
G1/8	8	2	8	5	162130018
G1/4	11	3	11	6	162130028
G3/8	12,5	3,5	14,5	8	162130038
G1/2	14	4	18	10	162130048
G3/4	14	3	21,5	12	162130068

ISO R - Plug 15005


Nickel plated brass



B	C	G		Model
R1/8	11	7,5	10	150050018
R1/4	15	11	14	150050028
R3/8	15,5	11,5	17	150050038
R1/2	18,5	14	22	150050048
R3/4	21,5	16,5	27	150050068
R1	25	19	34	150050088

ISO R - Plug 15113


Nickel plated brass



B	C	F		Model
R1/8	7,5	5	5	151130018
R1/4	10	7	6	151130028
R3/8	11	7	8	151130038
R1/2	13	8	10	151130048

ISO R - Plug 25013


Brass (unplated)



B	C	F		Model
R1/8	7,5	5	5	250130018
R1/4	10	7	6	250130028
R3/8	11	7	8	250130038
R1/2	13	8	10	250130048

ISO G and metric Elbow connector 16042


Nickel plated brass



B	E	G	Ø S		Typ
M5	11	5,5	-	9	1604200M5
G1/8	21	7	5,5	11	160420018
G1/4	25,5	8,5	8	13	160420028
G3/8	28	11	11	17	160420038
G1/2	32	15	15	20	160420048
G3/4	36,5	16,5	19	27	160420068
G1	45	19	24	30	160420088

ISO G - ISO R Elbow connector 15043


Nickel plated brass



B	B1	C	E	G	G1	Ø S		Model
M5	M5	11,5	11,5	4	5,5	-	9	1604300M5
R1/8	G1/8	21	18	7,5	8,5	5,5	12	150430018
R1/4	G1/4	25,5	24	11	11	8	13	150430028
R3/8	G3/8	28	27	11,5	12	11	16	150430038
R1/2	G1/2	32	29,5	14	15	15	20	150430048
R3/4	G3/4	36,5	32	14,5	16,5	19	27	150430068
R1	G1	45	39	16	19	24	30	150430088

ISO R - Elbow connector 15040


Nickel plated brass



B	E	G	Ø S		Model
R1/8	18	7,5	6	11	150400018
R1/4	24	11	8	13	150400028
R3/8	27	12	11	17	150400038
R1/2	29,5	14	15	20	150400048
R3/4	32	14,5	19	27	150400068
R1	39	17	24	30	150400088

ISO R - Tee connector 15060


Nickel plated brass



B	C	E	G	ØS		Model
R1/8	35	17,5	8	5,5	12	150600018
R1/4	46	23	11	8	13	150600028
R3/8	51,5	25,5	11,5	11	16	150600038
R1/2	59	29,5	14	15	20	150600048
R3/4	64	32	14,5	19	27	150600068
R1	78	39	17	24	30	150600088

ISO G - Tee connector 16062

Nickel plated brass




B	C	E	G	ØS		Model
G1/8	39	19,5	8,5	6	12	160620018
G1/4	49	24,5	11	8	13	160620028
G3/8	54	27	12	11	16	160620038
G1/2	64	32	15	15	20	160620048
G3/4	73	36,5	16,5	19	27	160620068
G1	90	45	19	24	30	160620088

Dimensions in mm
Projection/First angle



ISO R and Metric - ISO G - Tee connector 15072


Nickel plated brass



B	B1	C	E	G	G1		Model
M5	M5	22	11	4	5,5	9	1607200M5
G1/8	R1/8	37	19,5	8	8,5	12	150720018
G1/4	R1/4	47,5	24,5	11	11	13	150720028
G3/8	R3/8	52,5	27	11,5	12	16	150720038
G1/2	R1/2	61,5	32	14	15	20	150720048
G3/4	R3/4	68,5	36,5	14,5	16,5	27	150720068
G1	R1	84	45	17	19	30	150720088

ISO R and Metric - ISO G - Tee connector 15069


Nickel plated brass



B	B1	C	E	G	G1	ØS		Model
M5	M5	22	11	5,5	4	-	9	1606900M5
G1/8	R1/8	39	17,5	8,5	8	6	12	150690018
G1/4	R1/4	49	23	11	11	8	13	150690028
G3/8	R3/8	54	25,5	12	11,5	11	16	150690038
G1/2	R1/2	64	29	15	14	15	20	150690048
G3/4	R3/4	73	32	16,5	14,5	19	27	150690068
G1	R1	90	39	19	17	24	30	150690088

ISO G - Cross 16092


Nickel plated brass



B	C	G	ØS		Model
G1/8	39	8,5	6	11	160920018
G1/4	50	11	8	13	160920028
G3/8	56	12	11	17	160920038
G1/2	64	15	15	20	160920048

ISO G - Cross block 16094

Aluminium




B	C	ØD	E	H	Model
G1/8	25	4,5	17,5	16	160940018
G1/4	40	5,5	27	20	160940028
G3/8	50	5,5	35	25	160940038
G1/2	50	5,5	35	32	160940048

ISO G - Manifold - single sided 34050

Brass

Dimensions in mm
Projection/First angle



Numbers of outputs: 4


B	B1	C	ØD	E	E1	E2	F	H	J	J1	Model
G1/4	G1/4	109	5,5	31	5	20	23	23	20	5	34050402
G3/8	G3/8	127	6,5	35	6	23	27	25,5	20	6	34050403

Numbers of outputs: 6

B	B1	C	ØD	E	E1	E2	F	H	J	J1	Model
G1/4	G1/4	155	5,5	31	5	20	23	23	20	5	34050602

ISO G - Manifold - single sided 162B4 and 162B6

Aluminium



Numbers of outputs: 4


B	B1	C	ØD	E	E1	E2	F	H	J	J1	Model
G1/4	G1/8	125	4,5	24	6	9	30	18	17,5	32,5	162B42818
G3/8	G1/4	148	5,5	30	7	11	36	22	20	38	162B43828
G1/2	G3/8	170	5,5	35	7,5	13	40	26	25	45	162B44838

Numbers of outputs: 6

B	B1	C	ØD	E	E1	E2	F	H	J	J1	Model
G1/4	G1/8	185	4,5	24	6	9	30	18	17,5	32,5	162B62818
G3/8	G1/4	220	5,5	30	7	11	36	22	20	38	162B63828
G1/2	G3/8	250	5,5	35	7,5	13	40	26	25	45	162B64838

ISO G - Manifold - double sided 162C4 and 162C6

Aluminium



Numbers of outputs: 8


B	B1	C	ØD	E	E1	F	H	J	J1	Model
G1/4	G1/8	125	4,5	30	6	30	18	17,5	32,5	162C42818
G3/8	G1/4	148	5,5	38	7	36	22	20	38	162C43828
G1/2	G3/8	170	5,5	44	7,5	40	26	25	45	162C44838

Numbers of outputs: 12

B	B1	C	ØD	E	E1	F	H	J	J1	Model
G1/4	G1/8	185	4,5	30	6	30	18	17,5	32,5	162C62818
G3/8	G1/4	220	5,5	38	7	36	22	20	38	162C63828
G1/2	G3/8	250	5,5	44	7,5	40	26	25	45	162C64838

ISO G - Elbow banjo assembly regulating-out BSP parallel

16K51




B	B1	C	D	E	G	AF	Weight (g)	Model
G1/8	G1/8	20	12,5	31,5	5	12	30	16K511818
G1/4	G1/4	23,5	12,5	32,5	6	15	47	16K512828
G3/8	G3/8	26,5	12,5	42	8	19	74	16K513838
G1/2	G1/2	34,5	24,5	70,5	8	27	235	16K514848

ISO G - Banjo elbow non-regulating, BSP parallel to BSP parallel


16A51

Dimensions in mm
Projection/First angle



B	C	D	E	G	AF	Weight (g)	Model
G1/8	20	12,5	31	6	14	29	16A511818
G1/4	23,5	12,5	33,5	8	17	48	16A512828
G3/8	26,5	12,5	34	8	19	64	16A513838
G1/2	34	12,5	35	9	27	104	16A514848


Banjo elbow body 16051



B	Bolt size B	ØB1	ØK	D	C	Weight (g)	Model
G1/8	G1/8	9,8	14	14,5	20	14	160511818Z
G1/4	G1/4	13,2	18	14,5	23,5	21	160512828Z
G3/8	G3/8	16,7	21	14,5	26,5	27	160513838Z
G1/2	G1/2	21	44	14,5	34	44	160514848Z

Note: Banjo elbow bodies with suffix Z at the end of the model number are not interchangeable with the previous series without the suffix Z.

ISO G - Banjo bolt, non-regulating stacking 20A00, 20B00, 20C00





B	C	D	E	F	AF	Type	Weight (g)	Model
M5	18	5,5	4	-	8	Single	4	20A000005Z
G1/8	31	12,5	6	-	14	Single	15	20A000018Z
G1/4	33,5	12,5	8	-	17	Single	27	20A000028Z
G3/8	34	12,5	8	-	19	Single	37	20A000038Z
G1/2	35	12,5	9	-	27	Single	60	20A000048Z
G1/8	56	12,5	6	25	14	Double	26	20B000018Z
G1/4	58,5	12,5	8	25	17	Double	44	20B000028Z
G3/8	59	12,5	8	25	19	Double	64	20B000038Z
G1/4	61,5	12,5	8	25	17	Triple	42	20C000028Z
G3/8	62	12,5	8	25	19	Triple	62	20C000038Z

Note:

Banjo bolts are supplied with a spacing washer with integral retention lug. The washer must be installed with the mounting lug at the lowest position to ensure retention on to thread.



**ISO G - Banjo bolt,
regulating out,
20K00**



B	D	E	G	AF	Weight (g)	Model
G1/8	12,5	31,5	5	12	15	20K000018Z
G1/4	12,5	32,5	6	15	25	20K000028Z
G3/8	12,5	42	8	19	45	20K000038Z

**ISO G - Banjo bolt, regulating in,
BSP parallel
20L00**


Dimensions in mm
Projection/First angle



B	D	E	G	AF	Weight (g)	Model
G1/8	12,5	31,5	5	12	15	20L000018Z
G1/4	12,5	32,5	6	15	25	20L000028Z


Note: Banjo bolts, regulating, non-regulating and stacking with suffix Z at the end of the model number are not interchangeable with the previous series without the suffix Z.

**ISO G - Banjo bolt,
regulating bi-directional,
20M00**



B	D	E	G	AF	Weight (g)	Model
G1/8	12,5	31,5	5	12	17	20M000018Z
G1/4	12,5	32,5	6	15	27	20M000028Z


**ISO R - Elbow flow control,
regulating out
10TA0**



B	B1	C	C1	E Max	E1	G	ØK	AF	AF1	Weight (g)	Model
R1/8	Rc1/8	18.2	7.3	40.7	16.0	7.6	14.5	12	15	30	10TA01818
R1/4	Rc1/4	26.5	9.5	46.6	21.1	10.6	18.0	15	19	60	10TA02828
R3/8	Rc3/8	30.8	11.6	54.9	25.0	12.6	23.0	19	24	107	10TA03838
R1/2	Rc1/2	38.7	14.0	60.1	29.1	14.5	26.5	24	28	170	10TA04848

Material: Body - Zinc die-casting


**ISO G - Elbow flow control,
regulating out
10KA0**



B	C	C1	E Max	E1	G	ØK	AF	AF1	Weight (g)	Model
G1/8	17.7	7.3	40.7	14.8	6.0	14.5	8	15	31	10KA01818
G1/4	26.0	9.5	46.6	15.8	8.0	18	12	19	66	10KA02828
G3/8	30.3	11.6	54.9	18.4	8.0	23	15	24	117	10KA03838
G1/2	38.2	14.0	60.1	22.1	9.0	26.5	19	28	180	10KA04848

Material: Body - Zinc die-casting


ISO R - Pilot operated check valve 101GA



B	B1	B2	C	C1	E	E1	G	ØK	AF	AF1	AF2	Weight (g)	Model
R1/8	Rc1/8	M5	18.2	7.3	40.8	15.4	7.6	14.5	12	15	8	35	101GA1818
R1/4	Rc1/4	Rc1/8	26.5	9.5	48.9	21.1	10.6	18.0	17	19	12	75	101GA2828
R3/8	Rc3/8	Rc1/8	30.8	11.6	56.7	24.8	12.6	23.0	20	24	12	123	101GA3838
R1/2	Rc1/2	Rc1/4	38.7	14.0	70.6	31.0	14.5	26.5	24	28	17	207	101GA4848

Material: Body - Zinc die-casting


ISO G - Pilot operated check valve 102GA



B	B1	B2	C	C1	E	E1	G	ØK	AF	AF1	AF2	Weight (g)	Model
G1/8	G1/8	M5	17.7	7.3	40.8	16.2	5.1	14.5	12	15	8	35	102GA1818
G1/4	G1/4	G1/8	26.0	9.5	48.9	21.3	6.6	18.0	17	19	12	77	102GA2828
G3/8	G3/8	G1/8	30.3	11.6	56.7	24.8	7.2	23.0	20	24	12	128	102GA3838
G1/2	G1/2	G1/4	38.2	14.0	70.6	29.6	8.7	26.5	24	28	17	219	102GA4848

Material: Body - Zinc die-casting


ISO G - Pressure reduction valve 102GB



B	B1	C	C1	E	E1	G	ØK	AF	AF1	AF2	AF3	Weight (g)	Model
G1/8	G1/8	18.5	8.4	70	19.8	6.3	13	15	17	13	5	57	102GB1818
G1/4	G1/4	22.5	10.4	78	25.8	9.5	18	19	17	13	5	76	102GB2828
G3/8	G3/8	28.5	12.5	85.7	29	9.7	23	23	23	17	6	132	102GB3838
G1/2	G1/2	31	15.3	86.7	32	9.5	25	28	27	17	6	181	102GB4848

Materials: Body - PA, Banjo bolt - nickel plated brass


ISO G - Pressure sensor valve 102GD



ØA	B	C	C1	E	F	G	AF	Weight (g)	Model
4	G1/8	25	21	45.2	9.5	5.5	15	38	102GD0418
4	G1/4	29	21	47.2	9.5	6.5	19	55	102GD0428


Materials: Body - PA, Banjo bolt - nickel plated brass

**Plug - Stainless steel
66005**




B	C	G	AF	Weight (g)	Model
G 1/8	10	6,5	14	7	660050018
G 1/4	13	9	17	14	660050028
G 3/8	13,5	9,5	19	17	660050038
G 1/2	14,5	10	24	26	660050048

**Sleeve adaptor - Stainless steel
66022**




B	C	Ø K	AF	Weight (g)	Model
G 1/8	15	13,5	14	11	660221818
G 1/4	22	16,5	17	21	660222828
G 3/8	24	21,5	22	33	660223838
G 1/2	30	25,5	27	62	660224848

**Tee connector - Stainless steel
66062**



B	C	E	G	Ø K	Ø S	AF	Weight (g)	Model
G 1/8	37	18,5	8,5	18,5	6	12	32	660620018
G 1/4	49	24,5	11	24,5	8	12	50	660620028
G 3/8	54	27	12	27	11	15	77	660620038
G 1/2	64	32	15	32	15	20	146	660620048


**ISO G -
Copper sealing washer
480213**



A for thread	D	K	Model
G1/8	1,8	13,5	48021301
G1/4	1,8	17,6	48021302
G3/8	1,8	20,9	48021303
G1/2	1,8	26,4	48021304
G3/4	1,8	32,4	48021306
G1	1,8	38,9	48021308

Operating Pressure: 20 Bar (max)
Temperature: -10°C ... +80°C


**ISO G -
Bonded sealing washer
480215**



A for thread	D	K	Model
G1/8	2	15,9	48021501
G1/4	2	20,6	48021502
G3/8	2	23,8	48021503
G1/2	2	28,6	48021504
G3/4	2	34,9	48021506
G1	2,5	42,8	48021508

Operating Pressure: 128 Bar (max)
Temperature: -30°C ... +110°C

**ISO G -
Aluminium sealing washer
(supplied with ISO G male
connectors)**



A for thread	D	K
G1/8	1,5	14
G1/4	1,5	18
G3/8	1,5	21
G1/2	1,5	26
G3/4	2,5	32
G1	2,5	39,5

Operating Pressure: 20 Bar (max)
Temperature: -10°C ... +80°C

**PTFE - sealing tape
DB-R-12**



Warning

These products are intended for use in industrial compressed air systems only. Do not use these products where pressures and temperatures can exceed those listed under **»Technical features/ data«**.

Before using these products with fluids other than those specified, for non-industrial applications, life-support systems or other applications not within published specifications, consult Norgren Ltd.

Through misuse, age, or malfunction, components used in fluid power systems can fail in various modes.

The system designer is warned to consider the failure modes of all component parts used in fluid power systems and to provide adequate safeguards to prevent personal injury or damage to equipment in the event of such failure.

System designers must provide a warning to end users in the system instructional manual if protection against a failure mode cannot be adequately provided.

System designers and end users are cautioned to review specific warnings found in instruction sheets packed and shipped with these products.