

## Complete system ■ Type PT-RF-SET

B



Complete system in case PT-RF-SET

### Product Description

The PT-RF-SET complete system is compiled in different versions according to customer requirements. All complete systems are supplied in a handy carrying case containing individually shaped foam inserts for a maximum of 10 pressure transmitters and 10 process connection adaptors and offering space for the following components:

#### Standard Option

- 1x Reader-PT-RF
- up to 3 Pressure Transmitters PT-RF
- up to 3 Process Connection Adaptors SDA or SMD
- 1x Quickguide
- 1x USB 2.0 cable (1 m / 3.28 ft)
- 1x Power Supply incl. country-specific adaptors

### Order Codes

PT-RF - SET - 2 - 400 / 600 / 000 - B						
①	②	③	④	⑤	⑥	⑦
<div> <div>① Series and Type</div> <div>Series PT-RF</div> <div>PT-RF</div> </div>						
<div> <div>② Version</div> <div>Complete system in case</div> <div>SET</div> </div>						
<div> <div>③ Number of Pressure Transmitters in the Set</div> <div>1x pressure transmitter</div> <div>1</div> </div>						
<div> <div>2x pressure transmitter</div> <div>2</div> </div>						
<div> <div>3x pressure transmitter</div> <div>3</div> </div>						
<div> <div>④ Pressure Range / Version</div> <div>1<sup>st</sup> pressure transmitter</div> <div>see table</div> </div>						
<div> <div>⑤ Pressure Range / Version</div> <div>2<sup>nd</sup> Pressure Transmitter</div> <div>see table</div> </div>						
<div> <div>⑥ Pressure Range / Version</div> <div>3<sup>rd</sup> Pressure Transmitter</div> <div>see table</div> </div>						
<div> <div>⑦ Process Connection Adaptor</div> <div>Adaptor SDA for process connection G1/4 (B04)</div> <div>B</div> </div>						
<div> <div>Adaptor SMD for process connection 1/4NPT (N04)</div> <div>N</div> </div>						

### Pressure Transmitter: Pressure Range and Version

Pressure Range	Version of Pressure Transmitter
000	When ordering a complete system with one or two pressure transmitters, the pressure range for the 2 <sup>nd</sup> and 3 <sup>rd</sup> pressure transmitter is given as "000".
016	Version pressure transmitter: B00016 (pressure range: 0 ... 16 bar / 0 ... 232 PSI)
060	Version pressure transmitter: B00060 (pressure range: 0 ... 60 bar / 0 ... 870 PSI)
160	Version pressure transmitter: B00160 (pressure range: 0 ... 160 bar / 0 ... 2320 PSI)
400	Version pressure transmitter: B00400 (pressure range: 0 ... 400 bar / 0 ... 5801 PSI)
600	Version pressure transmitter: B00600 (pressure range: 0 ... 600 bar / 0 ... 8702 PSI)
e.g.	400 (400 bar)      600 (600 bar)      000 (0 bar)

## Spare Parts / Accessories



Case-Reader-PT-RF

### Product Description

In addition to the Charger-Set-Reader-PT-RF which is available as a spare part, the Case-PT-RF-Set is also available as an individual item for assembling a complete system later on.

The Case-Reader-PT-RF is available if only a storage case for the reading device is required. It only provides space for the reading device and the associated accessories (without pressure transmitters and process connection adaptors).

### Order Codes

Spare Parts / Accessories	
①	
① Spare Parts / Accessories	
Case, small	Case-Reader-PT-RF
Case, large	Case-PT-RF-SET
5 V DC / 1 A power supply incl. country-specific adaptors and USB 2.0 cable	Power-Supply-PT-RF-Reader-MULTI
Adaptor for pressure transmitter (B04)	SDA-20-G1/4-W3
Adaptor for pressure transmitter (N04)	SMD-20-1/4NPT-W3
Straight fitting with adaptor	SRS-G1/4-***-V-G-W3