

INTERPUMP Hypress 4SP

APPLICATIONS :



TFDM4SP



APPROVALS :

MED, DNV - GL, BV, MSHA

APPLICABLE SPECIFICATIONS

EN 856 4SP - ISO 3862 4SP

4 high tensile spiral high flexibility. MSHA cover. Exceeding burst requirements.

Inner tube: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 4 steel wire spirals.

Coverage: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.

Recommended fluids: Hydraulic fluids petroleum based (mineral oils), glycol-water based, water, lubricants.

working temperature: from -40 to +100° C petroleum based fluids (Intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Product number	ID		Dimension	OD	Max WP		Min BP		Min BR		Weight (approx)		FERRULE	
	mm	in	dash size		bar	psi	bar	psi	mm	inch	lb/ft	kg/m	TWO PIECES SKIVE	TWO PIECES NO SKIVE
TFDM4SP-04	6.4	1/4"	04	17.8	450	6525	1800	26100	150	5.906	0.398	0.592	0009-04	-
TFDM4SP-06	9.5	3/8"	06	21.2	445	6453	1780	25810	180	7.087	0.531	0.79	0009-06	-
TFDM4SP-08	12.7	1/2"	08	24.3	415	6018	1660	24070	230	9.055	0.632	0.94	0009-08	-
TFDM4SP-10	16	5/8"	10	28	350	5075	1400	20300	250	9.843	0.756	1.125	0009-10	-
TFDM4SP-12	19	3/4"	12	32	350	5075	1400	20300	300	11.811	1.006	1.497	0009-12	BMC2-12
TFDM4SP-16	25.4	1"	16	39.5	280	4060	1120	16240	340	13.386	1.445	2.15	0009-16	BMC1-16
TFDM4SP-20	31.8	1.1/4"	20	50.8	210	3045	840	12180	460	18.11	2.122	3.157	0009-20	BMC2-20
TFDM4SP-24	38.1	1.1/2"	24	57.2	185	2683	740	10730	560	22.047	2.495	3.713	0009-24	-
TFDM4SP-32	50.8	2"	32	69.8	165	2393	660	9570	660	25.984	3.273	4.87	0009-32	-

Marking: Available also embossed brand version. In case of order use code TFDM4SPN.

ih INTERPUMP  Hypress 4SP ISO 3862/EN 856 - DN 10 I.D. 3/8" - W.P. 445 BAR/6453