



**Test Coupling with 24° Taper / O-ring (DKO)
SKK-12 Type K**

A



Version A



Version B

Ordering Codes

***SKK*-12*-18L*-B*-K*-GS*-SK*-W3**

- * Type Test Coupling with Piston Valve **SKK**
- * Series STAUFF Test 12 **-12**
(Connection Thread S12,65 x 1,5)
- * Outside Tube Diameter acc. to dimension table **-18**
- * Series Light Series **L**
Heavy Series **S**
- * Seal Material NBR (Buna-N®) **-B**
FKM (Viton®) **-V**
EPDM **-E**
- * Connection 24° Taper / O-ring (DKO) **-K**
- * Design One-piece design (Version A) **-**
Screwed design (Version B) **-GS**
- * Protection Cap Knurled protection cap **-**
- * Material Code Steel, zinc/nickel-plated **-W3**
Stainless Steel V2A - 1.4305 (AISI 303) **-W4**
Stainless Steel V4A - 1.4571 (AISI 316 Ti) **-W5**

Series	PN (^{mm} / _{psi})	Pipe $\varnothing d$	Dimensions (^{mm} / _{in})			Thread	Version	Weight (^{kg} / _{lbs}) ca. per 100	Ordering Codes (Standard Option)
			l_3	Hex A	T				
L	315 4568	6	15,5	14	M12 x 1,5	A	6,40	SKK-12-06L-B-K-W3	
			.61	.55			14,08		
		8	15,5	17	M14 x 1,5	A	6,50	SKK-12-08L-B-K-W3	
			.61	.67			14,30		
		10	16,5	19	M16 x 1,5	A	7,90	SKK-12-10L-B-K-W3	
			.65	.75			17,38		
	12	17,5	22	M18 x 1,5	A	9,00	SKK-12-12L-B-K-W3		
		.69	.87			19,80			
	15	160 2320	22	21	27	M22 x 1,5	B	11,70	SKK-12-15L-B-K-GS-W3
				.83	1.06			25,74	
	18	28	25	19,5	32	M26 x 1,5	B	19,00	SKK-12-18L-B-K-GS-W3
				.77	1.26			41,80	
	22	35	30	20,5	36	M30 x 2	B	18,70	SKK-12-22L-B-K-GS-W3
				.81	1.42			41,14	
28	42	31	25	41	M36 x 2	B	24,70	SKK-12-28L-B-K-GS-W3	
			.98	1.61			54,34		
35	315 4568	30	30	50	M45 x 2	B	39,50	SKK-12-35L-B-K-GS-W3	
			1.18	1.97			86,90		
42	400 5801	31	31	60	M52 x 2	B	85,80	SKK-12-42L-B-K-GS-W3	
			1.22	2.36			189,16		
S	630 9137	6	14,5	17	M14 x 1,5	A	6,60	SKK-12-06S-B-K-W3	
			.57	.67			14,52		
		8	16,5	19	M16 x 1,5	A	7,70	SKK-12-08S-B-K-W3	
			.65	.75			16,94		
		10	16,5	22	M18 x 1,5	A	8,80	SKK-12-10S-B-K-W3	
			.65	.87			19,36		
	12	17,5	24	M20 x 1,5	A	10,50	SKK-12-12S-B-K-W3		
		.69	.94			23,10			
	14	400 5801	18	19,5	27	M22 x 1,5	B	12,40	SKK-12-14S-B-K-GS-W3
				.77	1.06			27,28	
	16	20	24	18	30	M24 x 1,5	B	13,70	SKK-12-16S-B-K-GS-W3
				.71	1.18			30,14	
	20	25	26	24	36	M30 x 2	B	19,80	SKK-12-20S-B-K-GS-W3
				.94	1.42			43,56	
25	315 4568	30	26	46	M36 x 2	B	35,20	SKK-12-25S-B-K-GS-W3	
			1.02	1.81			77,44		
30	315 4568	30	30	50	M42 x 2	B	41,70	SKK-12-30S-B-K-GS-W3	
			1.18	1.97			91,74		
38	315 4568	34	34	60	M52 x 2	B	63,20	SKK-12-38S-B-K-GS-W3	
			1.34	2.36			139,04		

With 24° Taper / O-ring (DKO) Connection acc. to ISO 8434-1 / DIN 2353

Alternative materials and surface finishings are available upon request. Contact STAUFF for further information.