



Union Nut for 37° Flared Tube Fittings Type FI-BM ▪ Series L / S



Ordering Codes

***FI-BM*-15*L*-W3**

* Union Nut for 37° Flared Tube Fittings

FI-BM

* Outside Tube Diameter D1 (in mm)

-15

* Series
Light Series
Heavy Series

L

S

* Material Code Steel, zinc/nickel-plated

-W3

Please contact STAUFF for alternative materials and surface finishings.

Series	Tube OD mm	PN bar	Dimensions mm				Weight kg ca. per 100	Ordering Codes
			Thread T	D1	L1	S1		
L	6	500	M 12 x 1,5	7,8	17	14	1,07	FI-BM-06L-W3
	8	500	M 14 x 1,5	9,5	18	17	1,82	FI-BM-08L-W3
	10	500	M 16 x 1,5	11,7	19,5	19	2,35	FI-BM-10L-W3
	12	400	M 18 x 1,5	13,8	20,5	22	3,36	FI-BM-12L-W3
	15	400	M 22 x 1,5	17,7	23	27	5,31	FI-BM-15L-W3
	18	400	M 26 x 1,5	21,2	23	32	7,22	FI-BM-18L-W3
	22	250	M 30 x 2	24,4	27,5	36	10,60	FI-BM-22L-W3
	28	250	M 36 x 2	30,4	27,5	41	11,47	FI-BM-28L-W3
	35	250	M 45 x 2	38,3	30	50	16,27	FI-BM-35L-W3
	42	250	M 52 x 2	45,3	34	60	30,39	FI-BM-42L-W3
S	6	630	M 14 x 1,5	7,8	18	17	2,03	FI-BM-06S-W3
	8	630	M 16 x 1,5	9,5	19	19	2,52	FI-BM-08S-W3
	10	630	M 18 x 1,5	11,7	20,5	22	3,58	FI-BM-10S-W3
	12	630	M 20 x 1,5	13,8	21	24	4,11	FI-BM-12S-W3
	14	630	M 22 x 1,5	17,7	23	27	5,38	FI-BM-14S-W3
	16	630	M 24 x 1,5	18,7	26,5	30	7,87	FI-BM-16S-W3
	20	400	M 30 x 2	24,4	27,5	36	10,61	FI-BM-20S-W3
	25	400	M 36 x 2	28,7	30,5	46	22,19	FI-BM-25S-W3
	30	400	M 42 x 2	34,2	32	50	23,20	FI-BM-30S-W3
	38	400	M 52 x 2	42,3	38	60	35,40	FI-BM-38S-W3

Union Nut for 37° Flared Tube Fittings: DIN 3949

