




Blanking Plug for Tube Ends Type FI-VSK ▪ Series L / S



Ordering Codes

FI-VSK-10*L*-W3*-MS

* Blanking Plug for Tube Ends	FI-VSK
* Outside Tube Diameter D1 (in mm)	-10
* Series	Light Series L Heavy Series S
* Material Code	Steel, zinc/nickel-plated -W3
Please contact STAUFF for alternative materials and surface finishings.	
* Assembling / Kitting	Blanking plug only —
	Blanking plug supplied with cutting ring and union nut -MS
	Blanking plug supplied with soft-sealing cutting ring and union nut -MSV

Series	Tube OD mm D1	PN bar	Dimensions mm					Weight kg ca. per 100	Ordering Codes ³
			L	L1 ¹	L2	S1	S2		
L	6	500	17	22	7	14	14	1,40	FI-VSK-06L-W3
	8	500	17	23	8	17	17	1,93	FI-VSK-08L-W3
	10	500	20	24	9	17	19	2,55	FI-VSK-10L-W3
	12	400	21	25	10	19	22	3,44	FI-VSK-12L-W3
	15	400	20	26	11	24	27	4,90	FI-VSK-15L-W3
	18	400	21	28	11,5	27	32	6,80	FI-VSK-18L-W3
	22	250	23	30	13,5	32	36	10,70	FI-VSK-22L-W3
	28	250	23	31	14,5	41	41	15,20	FI-VSK-28L-W3
	35	250	29	36	14,5	46	50	25,90	FI-VSK-35L-W3
	42	250	30	39	16	55	60	35,30	FI-VSK-42L-W3
S	6	800	17	26	11	17	17	1,80	FI-VSK-06S-W3
	8	800	17	28	13	17	19	2,16	FI-VSK-08S-W3
	10	800	20	29	12,5	19	22	3,34	FI-VSK-10S-W3
	12	630	21	31	14,5	22	24	4,60	FI-VSK-12S-W3
	14	630	23	34	16	24	27	5,88	FI-VSK-14S-W3
	16	630	24	34	15,5	27	30	7,54	FI-VSK-16S-W3
	20	420	28	39	17,5	32	36	12,50	FI-VSK-20S-W3
	25	420	31	44	20	41	46	21,40	FI-VSK-25S-W3
	30	420	34	47	20,5	46	50	30,40	FI-VSK-30S-W3
	38	420	38	54	23	55	60	40,80	FI-VSK-38S-W3

¹ Approximate dimension in assembled condition.

² Weight excluding cutting ring and union nut.

³ Standard scope of delivery: Blanking plug only.

Connecting Parts



Cutting Ring
Type **FI-DS** Page 28



Soft-Sealing Cutting Ring
Type **FI-WDDS** Page 29



Support Sleeve
Type **FI-VH** Page 31



STAUFF Form EVO Sealing Ring
Type **FI-FD** Page 32



Union Nut
Type **FI-M** Page 33



37° Flared Tube Fitting Set
Type **FI-AB** Page 37

